

Potential operations in the **gRain** package

Søren Højsgaard

May 1, 2008

Contents

1	Potentials and operations on these	1
1.1	Implementation of potentials	2
1.2	Examples	2
1.3	Operations on potentials	3
1.4	Examples	3
1.5	Coercion	4

1 Potentials and operations on these

Consider a set $\Delta = \{\delta_1, \dots, \delta_R\}$ of discrete variables where δ_r has a finite set I_r of levels. Let $|I_r|$ denote the number of levels of δ_r and let $i_r \in I_r$ denote a value of δ_r . A configuration of the variables in Δ is then $i = (i_1, \dots, i_R) \in I_1 \times \dots \times I_R$. The total number of configurations is then $|\Delta| = \prod_r |I_r|$. Let U be a non-empty subsets of Δ with configurations I_U and let i_U denote a specific configuration.

A potential T_U defined on I_U is a non-negative function, i.e. $T_U(i_U) \geq 0$ for all $i_U \in I_U$.

Let U and V be non-empty subsets of Δ with configurations I_U and I_V and let T_U^1 and T_V^2 be corresponding potentials.

The product (quotient) of T_U^1 and T_V^2 are potentials defined on $U \cup V$ given by

$$T_{U \cup V} := T_U^1 \times T_V^2 \text{ and } T_{U \cup V} := T_U^1 / T_V^2$$

respectively, with the convention that $0/0 = 0$. If $V \subset U$ is non-empty¹ then marginalization of T_U^1 onto V is defined as

$$T_V^1 := \sum_{U \setminus V} T_U^1$$

¹Marginalization onto an empty set is not implemented.

1.1 Implementation of potentials

Potentials are represented by `ptab` objects which are defined as part of the `gRain` package. `ptab` objects are essentially arrays, and the only reason for not simply working with arrays implementing a special class is a pure technicality: Two-dimensional arrays are (correctly) in some respects regarded as matrices while one-dimensional arrays are (correctly) in some respects regarded as vectors. For our purpose we need a class of objects which are regarded as being of the same type irrespectively of their dimension. However we may for all practical purposes think of `ptab` objects as arrays.

1.2 Examples

`ptab` objects can be created as:

```
> yn <- c("y", "n")

[1] "y" "n"

> a.1 <- ptab("asia", list(yn), values = c(1, 99))

asia
  y  n
1 99

> t.a.1 <- ptab(c("tub", "asia"), list(yn, yn), values = c(5, 95, 1, 99))

      asia
tub  y  n
y   5  1
n  95 99
```

Tables can be normalized in two ways: Either the values are normalized over all configurations to sum to one as

```
> a.2 <- ptab("asia", list(yn), values = c(1, 99), normalize = "all")

asia
  y  n
0.01 0.99
```

Alternatively normalization can be over the first variable for *each* configuration of all other variables as

```
> t.a.2 <- ptab(c("tub", "asia"), list(yn, yn), values = c(5, 95, 1, 99), normalize = "first")

      asia
tub  y  n
y 0.05 0.01
n 0.95 0.99
```

1.3 Operations on potentials

Multiplication and division of potentials is implemented as follows. Consider multiplication of ϕ_U and ψ_V .

The vectors, say T_U and T_V , containing the values of the potentials are given a dimension attribute, i.e. are turned into arrays.

Assume first that $V \subset U$. Then we reorder the elements of T_U to match with those of T_V , symbolically as $(V, U \setminus V)$ so that we have tables T_V into $T_{V, U \setminus V}$ accordingly. This operation is fast with the `aperm()` function which is implemented in C. We can then form the product $T_{V, U \setminus V} T_V$ directly because the elements of T_V are recycled to match the length of $T_{V, U \setminus V}$. If V is not a subset of U then we expand the domain of T_U into $T_{V, U \setminus V}$ by first permuting the array with `aperm()` and then repeating the entries a suitable number of times and then carry out the multiplications as above.

Marginalization is similarly based on using `apply()` where summation is over a specific set of dimensions.

1.4 Examples

Hence we can calculate the joint, the marginal and the conditional distributions as

```
> ta.1 <- arrayop(t.a.1, a.1, op = "*")
> ta.1

      tub
asia y   n
y   5   95
n  99 9801

> arraymarg(ta.1, "tub")

      tub
      y   n
104 9896

> arrayop(ta.1, arraymarg(ta.1, "tub"), op = "/")

      asia
tub    y      n
y 0.048076923 0.9519231
n 0.009599838 0.9904002
```

The `ptab` function takes a `smooth` argument which by default is 0. A non-zero value of `smooth` implies that zeros in `values` are replaced by the value of `smooth` – before any normalization is made, e.g.

```
> ptab(c("tub", "asia"), list(c("y", "n"), c("y", "n")), values = c(0, 95, 0,
+ 99), normalize = "first", smooth = 1)

      asia
tub      y      n
y 0.01041667 0.01
n 0.98958333 0.99
```

It is possible to take out a sub-array defined by specific dimensions being at specific levels. This corresponds finding a specific slice of a multidimensional array: To find the 1-dimensional array defined by asia (variable 1) being “no” (at level 2) do:

```
> ta.1

      tub
asia y      n
y  5    95
n 99 9801

> subarray(ta.1, margin = 1, index = 2)

tub
y      n
99 9801
```

1.5 Coercion

Coercion to `ptab` is done by `as.ptab`. For example:

```
> v <- 1:4
> as.ptab(v)

V1
V11 V12 V13 V14
1   2   3   4

> names(v) <- c("a1", "a2", "a3", "a4")
> as.ptab(v)

V1
V11 V12 V13 V14
1   2   3   4
```

```

> v <- array(1:4, c(4))
> as.ptab(v)

V1
V11 V12 V13 V14
  1   2   3   4

> v <- array(1:4, c(4), dimnames = list(a = c("a1", "a2", "a3", "a4")))
> as.ptab(v)

a
a1 a2 a3 a4
  1  2  3  4

```

```

> v <- array(1:4, c(2, 2))
> as.ptab(v)

      V2
V1    V21 V22
V11   1   3
V12   2   4

> v <- array(1:4, c(2, 2), dimnames = list(a = c("a1", "a2"), b = c("b1", "b2")))
> as.ptab(v)

      b
a     b1 b2
a1   1   3
a2   2   4

```

```

> v <- array(1:8, c(2, 2, 2))
> as.ptab(v)

, , V3 = V31

      V2
V1     V21 V22
V11    1   3
V12    2   4

, , V3 = V32

      V2
V1     V21 V22
V11    5   7
V12    6   8

> v <- array(1:4, c(2, 2, 2), dimnames = list(a = c("a1", "a2"), b = c("b1", "b2"),
+      c = c("c1", "c2")))
> as.ptab(v)

, , c = c1

      b
a      b1 b2
a1    1   3
a2    2   4

, , c = c2

      b
a      b1 b2
a1    1   3
a2    2   4

```