

Package ‘eva3dm’

November 25, 2024

Type Package

Title Evaluation of 3D Meteorological and Air Quality Models

Version 0.99.1

Date 2024-11-24

Description Provides tools for post-process, evaluate and visualize results from 3d Meteorological and Air Quality models against point observations (i.e. surface stations) and grid (i.e. satellite) observations.

Maintainer Daniel Schuch <underschuch@gmail.com>

License MIT + file LICENSE

Imports terra, ncdf4, utils

Suggests riem, testthat (>= 3.0.0)

Encoding UTF-8

BugReports <https://github.com/Schuch666/eva3dm/issues/>

RxygenNote 7.3.2

Depends R (>= 3.5.0)

URL <https://schuch666.github.io/eva3dm/>

Config/testthat.edition 3

NeedsCompilation no

Author Daniel Schuch [aut, cre] (<<https://orcid.org/0000-0001-5977-4519>>)

Repository CRAN

Date/Publication 2024-11-25 08:50:02 UTC

Contents

atr	2
cate	3
daily	5
eva	6
extract_max_8h	8

extract_mean	9
extract_serie	10
get_distances	12
hourly	12
interp	14
legend_range	15
ma8h	16
mda8	17
ncdump	18
overlay	18
plot_diff	20
plot_rast	21
q2rh	22
rain	23
rast_to_netcdf	24
read_stat	25
rh2q	25
sat	26
stat	28
template	29
uv2wd	30
uv2ws	32
vars	33
wrf_rast	33
write_stat	35
%IN%	36
%at%	37

Index**38**

atr	<i>Read and write attributes on a NetCDF file</i>
-----	---

Description

Read and write metadata information of a NetCDF files

Usage

```
atr(file = NA, var = "?", att = NA, action = "get", value = NA, verbose = TRUE)
```

Arguments

file	file name
var	variable name, 0 to global and "?" to show options
att	attribute names (NA for get all attnames)
action	"get" (default), "write" or "print" (return the value) of an attribute

value	value to write
verbose	display additional information

Value

string with the NetCDF attribute value

Examples

```
nc <- paste0(system.file("extdata", package="eva3dm"), '/wrfinput_d01')
atr(nc,0)
atr(nc,'Times')
atr(nc,'XLAT')
atr(nc,'XLONG')

atr(nc,'XLONG','MemoryOrder')
atr(nc,'XLONG','description')
atr(nc,'XLONG','units')
atr(nc,'XLONG','stagger')
atr(nc,'XLONG','FieldType')
```

cate

Calculate categorical statistics in related to a threshold

Description

Calculate traditional statistics related to a threshold

Usage

```
cate(
  model,
  observation,
  threshold,
  cutoff = NA,
  nobs = 8,
  rname,
  to.plot = FALSE,
  col = "#4444bb",
  pch = 19,
  lty = 3,
  lcol = "#333333",
  lim,
  verbose = TRUE,
  ...
)
```

Arguments

<code>model</code>	numeric vector with paired model data
<code>observation</code>	numeric vector with paired observation data
<code>threshold</code>	reference value
<code>cutoff</code>	(optionally the maximum) valid value for observation
<code>nobs</code>	minimum number of observations
<code>rname</code>	row name
<code>to.plot</code>	TRUE to plot a scatter-plot
<code>col</code>	color for points
<code>pch</code>	pch of points
<code>lty</code>	lty of threshold lines
<code>lcol</code>	col of threshold lines
<code>lim</code>	limit for x and y
<code>verbose</code>	display additional information
<code>...</code>	arguments passed to plot

Value

a data.frame including: Accuracy (A); Critical Success Index (CSI); Probability of Detection (POD); Bias(B); False Alarm Ratio (FAR); Heidke Skill Score (HSS); Pearce skill Score (PSS) in

References

Yu, S., Mathur, R., Schere, K., Kang, D., Pleim, J., Young, J., ... & Rao, S. T. (2008). Evaluation of real-time PM2. 5 forecasts and process analysis for PM2. 5 formation over the eastern United States using the Eta-CMAQ forecast model during the 2004 ICARTT study. *Journal of Geophysical Research: Atmospheres*, 113(D6).

Examples

```
data <- 0.02 * 1:100
set.seed(666)
model <- abs(rnorm(100,0.01))

oldpar <- par(pty="s")
cate(model = model, observation = data, threshold = 1,
     to.plot = TRUE, rname = 'example')
par(oldpar)
```

daily	<i>Calculate daily mean, min or max</i>
-------	---

Description

function to calculate daily mean, min or max of a data.frame

Usage

```
daily(  
  data,  
  time = "date",  
  var,  
  stat = mean,  
  min_offset = 0,  
  hour_offset = 0,  
  numerical = TRUE,  
  verbose = TRUE  
)
```

Arguments

data	data.frame with time column and variable columns to be processed
time	name of the time column (default is date) in POSIXct
var	name of the columns to be calculated
stat	function of the statistics to calculate (default is mean)
min_offset	minutes of observation from previous hour (default is 0)
hour_offset	hours of observation from previous day (default is 0)
numerical	TRUE (defoult) include only numerical columns
verbose	display additional information

Value

data.frame with time and the daily mean, min or max

Examples

```
sites <- c("OAKB")  
for(site in sites){  
  cat('downloading METAR from:',site,'...\n')  
  DATA <- riem::riem_measures(station    = sites,  
                               date_start = "2012-01-01",  
                               date_end   = "2012-02-01")  
}  
data_daily_mean <- daily(DATA,time = 'valid')  
data_daily_min  <- daily(DATA[1:7],time = 'valid',stat = min)
```

```
data_daily_max <- daily(DATA[1:7], time = 'valid', stat = max)
```

eva*Model statistical evaluation***Description**

Statistical (or categorical) evaluation from 2 data.frames. The input data.frames (model and observation) must contain a "date" column (containing POSIXlt). The function perform some simple case tests and perform the time pairing of observations and model data and can calculate the statistical evaluation or categorical evaluation.

Usage

```
eva(
  mo,
  ob,
  rname = site,
  table = NULL,
  site = "ALL",
  wd = FALSE,
  fair = NULL,
  cutoff = NA,
  cutoff_NME = NA,
  no_tz = FALSE,
  nobs = 8,
  eval_function = stat,
  time = "date",
  verbose = TRUE,
  ...
)
```

Arguments

mo	data.frame with model data
ob	data.frame with observation data
rname	row name of the output (default is site argument)
table	data.frame to append the results
site	name of the stations or "ALL" (default), see notes
wd	default is FALSE, see notes
fair	model data.frame (or list of names) to perform a fair comparison, see notes
cutoff	minimum (optionally the maximum) valid value for observation
cutoff_NME	minimum (optionally the maximum) valid value for observation for NME
no_tz	ignore tz from input (force GMT)

nobs	minimum number of valid observations, default is 8
eval_function	evaluation function (default is stat)
time	name of the time column (containing time in POSIXct)
verbose	display additional information
...	arguments to be passing to stats and plot

Value

data.frame with statistical values from stat or cate functions.

Note

fair can be a data.frame or a character string to be used for the analysis, alternatively the function for wind direction a rotation of 360 (or -360) is applied to minimize the wind direction difference. If site == 'ALL' (default) all the columns from observations are combined in one column (same for observation) and all the columns are evaluated together.

Special thanks to Kiarash and Libo to help to test the wind direction option.

See Also

[stat](#) for additional information about the statistical evaluation and [cate](#) for categorical evaluation.

Examples

```
model <- readRDS(paste0(system.file("extdata", package="eva3dm"),
                         "/model.Rds"))
obs   <- readRDS(paste0(system.file("extdata", package="eva3dm"),
                         "/obs.Rds"))

# if there is no observed data
# the function return an empty row
table <- eva(mo = model, ob = obs, site = "VVIbes")
print(table)

# if the site are not in the input data frame a message is displayed
# and the function return an empty row
table <- eva(mo = model, ob = obs, site = "Ibirapuera")
print(table)

# calculating statistical with a few observed values
table <- eva(mo = model, ob = obs, site = "Americana")
print(table)

# calculating categorical (using 2 for threshold) with a few observed values
table <- eva(mo = model, ob = obs, site = "Americana",
             eval_function = cate, threshold = 2)
print(table)

# calculating categorical (using 2 for threshold) with a few observed values
```

```
table <- eva(mo = model, ob = obs, site = "Americana",
             eval_function = cate, threshold = 10)
print(table)
```

extract_max_8h*Create a NetCDF file with the surface maximum of O3***Description**

Read the values from o3 and T2, convert o3 to ug m-3 and calculate the maximum of 8-hour moving avarage from a list of files.

Usage

```
extract_max_8h(
  filelist,
  variable = "o3",
  field = "4d",
  prefix = "max_8h",
  units = "ug m-3",
  meta = TRUE,
  filename,
  verbose = TRUE
)
```

Arguments

filelist	list of files to be read
variable	variable name
field	'4d' (default), '3d', '2d' or '2dz' see notes
prefix	to output file, default is serie
units	units on netcdf file (default is ug m-3), change to skip unit conversion
meta	use Times, XLONG and XLAT data (only works with 2d variable for file)
filename	name for the file, in this case prefix is not used
verbose	display additional information

Value

No return value

Note

The field argument '4d' / '2dz' is used to read a 4d/3d variable droping the 3rd dimention (z).

Examples

```
dir.create(file.path(tempdir(), "MDA8"))
folder <- system.file("extdata", package="eva3dm")
wrf_file <- paste0(folder, "/test_small_o3.nc")
extract_max_8h(filelist = wrf_file,
                prefix = paste0(file.path(tempdir(), "MDA8"), '/mean'),
                field = '3d')
```

extract_mean

Create a NetCDF file with the surface mean

Description

Read and calculate the mean value of a variable from a list of wrf output files.

Usage

```
extract_mean(
  filelist,
  variable = "o3",
  field = "4d",
  prefix = "mean",
  units = "ppmv",
  meta = TRUE,
  filename,
  verbose = TRUE
)
```

Arguments

filelist	list of files to be read
variable	variable name
field	'4d' (default), '3d', '2d' or '2dz' see notes
prefix	to output file, default is serie
units	units on netcdf file (default is ppmv)
meta	use Times, XLONG and XLAT data (only works with 2d variable for file)
filename	name for the file, in this case prefix is not used
verbose	display additional information

Value

No return value

Note

The field argument '4d' / '2dz' is used to read a 4d/3d variable droping the 3rd dimension (z).

Examples

```
dir.create(file.path(tempdir(), "MEAN"))
folder <- system.file("extdata", package="eva3dm")
wrf_file <- paste0(folder, "/wrf.day1.o3.nc")
extract_mean(filelist = wrf_file, prefix = paste0(file.path(tempdir(), "MEAN"), '/mean'))
```

extract_serie

Extract time series of wrf file list of lat/lon

Description

Read and extract data from a list of wrf output files and a table of lat/lon points based on the distance of the points and the center of model grid points, points outside the domain (and points on domain boundary) are not extracted.

Usage

```
extract_serie(
  filelist,
  point,
  variable = "o3",
  field = "4d",
  prefix = "serie",
  new = "check",
  return.nearest = FALSE,
  fast = FALSE,
  use_ij = FALSE,
  latitude = "XLAT",
  longitude = "XLONG",
  use_TFLAG = FALSE,
  use_datesec = FALSE,
  id = "id",
  verbose = TRUE
)
```

Arguments

filelist	list of files to be read
point	data.frame with lat/lon
variable	variable name
field	'4d' (defoult), '3d', '2d' or '2dz' see notes

<code>prefix</code>	to output file, default is serie
<code>new</code>	TRUE, FALSE of 'check' see notes
<code>return.nearest</code>	return the data.frame of nearest points instead of extract the serie
<code>fast</code>	faster calculation of grid distances but less precise
<code>use_ij</code>	logical, use i and j from input instead of calculate
<code>latitude</code>	name of latitude coordinate variable in the netcdf
<code>longitude</code>	name of longitude coordinate variable in the netcdf
<code>use_TFLAG</code>	use the variable TFLAG (CMAQ / smoke) instead of Times (WRF)
<code>use_datesec</code>	use the variable date and datesec (WACCM / CAM-Chem) instead of Times (WRF)
<code>id</code>	name of the column with station names, if point is a SpatVector (points) from terra package
<code>verbose</code>	display additional information

Value

No return value

Note

The field argument '4d' or '2dz' is used to read a 4d/3d variable droping the 3rd dimension (z).
`new = TRUE` create a new file, `new = FALSE` append the data in a old file, and `new = 'check'` check if the file exist and append if the file exist and create if the file doesn't exist
FOR CAMx time-series, use the options: `use_TFLAG=T, latitude='latitude', longitude='longitude', new=T`
FOR WACCM time-series, use the options: `use_datesec=T, latitude='lat', longitude='lon', new=T`
The site-list of two global data-sets (METAR and AERONET) are provided on examples and site-list for stations on Brazil (INMET and Air Quality stations).

Examples

```

cat('Example 1: METAR site list\n')
sites <- readRDS(paste0(system.file("extdata",package="eva3dm"),"/sites_METAR.Rds"))

cat('Example 2: AERONET site list\n')
sites <- readRDS(paste0(system.file("extdata",package="eva3dm"),"/sites_AERONET.Rds"))

cat('Example 3: list of INMET stations on Brazil\n')
sites <- readRDS(paste0(system.file("extdata",package="eva3dm"),"/sites_INMET.Rds"))

cat('Example 4: list of Air Quality stations on Brazil\n')
sites <- readRDS(paste0(system.file("extdata",package="eva3dm"),"/sites_AQ_BR.Rds"))

files   <- dir(path = system.file("extdata",package="eva3dm"),
               pattern = 'wrf.day',
               full.names = TRUE)

```

```
dir.create(file.path(tempdir(),"SERIE"))
folder <- file.path(tempdir(),"SERIE")

# extract data for 3 locations
extract_serie(filelist = files, point = sites[1:3,],prefix = paste0(folder,'/serie'))
```

get_distances *Get the distance in kilometers between two points*

Description

Get the distance in kilometers between two points

Usage

```
get_distances(lat1, long1, lat2, long2, R = 6371)
```

Arguments

lat1	Latitude in decimals
long1	Longitude in decimals
lat2	Latitude in decimals
long2	Longitude in decimals
R	Radius of the earth in kmdescription (R=6371)

Value

A numeric vector with the distance in kilometers.

#' source: https://github.com/gustavobio/brclimate/blob/master/R/get_distances.R

hourly *Calculate hourly mean, min or max*

Description

function to calculate Ozone Maximum Daily 8-hr Average or 8-hr moving Average for a data.frame

Usage

```
hourly(
  data,
  time = "date",
  var,
  stat = mean,
  min_offset = 30,
  numerical = TRUE,
  verbose = TRUE
)
```

Arguments

<code>data</code>	data.frame with time column and variable columns to be processed
<code>time</code>	name of the time column (default is date) in POSIXct
<code>var</code>	name of the columns to be calculated
<code>stat</code>	function of the statistics to calculate (default is mean)
<code>min_offset</code>	minutes of observation from previous hour (default is 30)
<code>numerical</code>	TRUE (default) includes only numerical columns
<code>verbose</code>	display additional information

Value

`data.frame` including only numerical columns
`data.frame` with time and the hourly mean, min or max

Examples

```
sites <- c("OAGR")
for(site in sites){
  cat('downloading METAR from:',site,'...\n')
  DATA <- riem::riem_measures(station    = sites,
                               date_start = "2012-01-01",
                               date_end   = "2012-02-01")
}
data_hourly_mean <- hourly(DATA,time = 'valid')
data_hourly_min <- hourly(DATA[1:7],time = 'valid',stat = min)
data_hourly_max <- hourly(DATA[1:7],time = 'valid',stat = max)
```

interp*Interpolation (project and resample)*

Description

function to project and interpolate rast

Usage

```
interp(x, y, method = "bilinear", mask, verbose = FALSE)
```

Arguments

x	rast to be interpolated
y	target rast of the interpolation
method	passed to terra::resample
mask	optional SpatVector to mask the results
verbose	display additional information (not used)

Value

SpatRaster (terra package)

Examples

```
model_o3 <- terra::rast(paste0(system.file("extdata", package="eva3dm"),
                                "/camx_no2.Rds"))
omi_o3   <- terra::rast(paste0(system.file("extdata", package="eva3dm"),
                                "/omi_no2.Rds"))

# interpolate omi O3 column to model grid
omi_o3c_interp_model <- interp(omi_o3, model_o3)

# interpolate model O3 column to omi grid
model_o3c_interp_omi <- interp(model_o3, omi_o3)
```

legend_range	<i>Plot a legend with the range of values</i>
--------------	---

Description

Plot a legend with the range of values

Usage

```
legend_range(  
  x,  
  y,  
  text.width = NULL,  
  dig = c(2, 2, 2),  
  xjust = 0.005,  
  yjust = 0.95,  
  horiz = TRUE,  
  y.intersp = 0.5,  
  x.intersp = 0.5,  
  show.mean = TRUE,  
  unit = "",  
  label_mean = "ALL:",  
  ...  
)
```

Arguments

x	rast or array
y	rast or array to mean (x is used only for the range in this case)
text.width	Longitude in decimals
dig	vector with number of digits for plot
xjust	passed to legend
yjust	passed to legend
horiz	passed to legend
y.intersp	passed to legend
x.intersp	passed to legend
show.mean	set TRUE to hide mean value
unit	a string for units
label_mean	label in case y is provided
...	extra arguments passed to legend

Value

No return value

Note

for use with rast use before any change of projection
text.width can vary depending on map dimensions

Examples

```
x <- 1:10 + rnorm(10, sd = .4)
plot(x, ty='l')
legend_range(x)
```

ma8h

*Calculate 8-hour moving average***Description**

function to calculate Ozone 8-hour moving average for a data.frame

Usage

```
ma8h(data, time = "date", var, verbose = TRUE, ...)
```

Arguments

data	data.frame with time column and variable columns to be processed
time	name of the time column (default is date) in POSIXct
var	name of the columns to be calculated
verbose	display additional information
...	parameters passed to hourly

Value

data.frame with time and the 8-hour moving average

Examples

```
model_file <- paste(system.file("extdata", package = "eva3dm"),
                     "/model_o3_ugm3_36km.Rds", sep="")
model      <- readRDS(model_file)
model_8h   <- ma8h(model)
plot(model$date,model$Campinas, pch = 19,
      main = expression(O[3]~~'[*mu*g*m^-3*']))
points(model_8h$date,model_8h$Campinas, col = 'blue', pch = 19)
legend('topleft', bty = 'n',
       pch = 19,
       legend = c('hourly','8h-mov average'),
       col = c('black','blue'))
```

mda8	<i>Maximum Daily 8-hr Average</i>
------	-----------------------------------

Description

function to calculate Ozone Maximum Daily 8-hr Average or 8-hr moving Average for a data.frame

Usage

```
mda8(data, time = "date", var, verbose = TRUE)
```

Arguments

data	data.frame with time column and variable columns to be processed
time	name of the time column (default is date) in POSIXct
var	name of the columns to be calculated
verbose	display additional information

Value

data.frame with time and the maximum daily 8-hr average

Examples

```
model_file <- paste(system.file("extdata", package = "eva3dm"),
                     "/model_o3_ugm3_36km.Rds", sep="")
model      <- readRDS(model_file)
model_mda8 <- mda8(model)
model_8h   <- ma8h(model)
plot(model$date,model$Campinas, pch = 19,
      main = expression(0[3]~['*mu*g*m^-3*']))
points(model_8h$date,model_8h$Campinas, col = 'blue', pch = 19)
points(model_mda8$date + 17*60*60,model_mda8$Campinas,
       col = 'red', pch = 4, cex = 2)
legend('topleft', bty = 'n',
       pch = c(19,19,4),
       legend = c('hourly','8h-mov average','MD8A'),
       col = c('black','blue','red'))
```

ncdump	<i>Print a 'ncdump -h' command</i>
--------	------------------------------------

Description

Read a NetCDF and print the medatada

Usage

```
ncdump(file = file.choose())
```

Arguments

file	file name
------	-----------

Value

No return value, only display information

Examples

```
ncdump(file = paste0(system.file("extdata", package="eva3dm"),
  '/wrfinput_d01'))
```

overlay	<i>Plot or add points using a color scale</i>
---------	---

Description

Custon plot for SpatRaster (terra R-package) object based on terra package

Usage

```
overlay(
  p,
  z,
  col,
  lim = range(z, na.rm = TRUE),
  symmetry = TRUE,
  pch = 19,
  cex = 1,
  outside = TRUE,
  add = FALSE,
  plg = list(tic = "none", shrink = 1),
  pax = list(),
```

```
expand = 1.15,
...
)
```

Arguments

p	SpatVector points
z	column name or a vector of values to plot
col	color
lim	range of values for scale
symmetry	calculate symmetrical scale
pch	type of point
cex	character expansion for the points
outside	to include values outside range
add	add to existing plot
plg	list of parameters passed to terra::add_legend
pax	list of parameters passed to graphics::axis
expand	to expand the plot region
...	arguments to be passing to terra::plot

Value

No return value

Examples

```
sp<- terra::vect(paste0(system.file("extdata",package="eva3dm"),"/masp.shp"))
BR<- terra::vect(paste0(system.file("extdata",package="eva3dm"),"/BR.shp"))

p      <- readRDS(paste0(system.file("extdata",package="eva3dm"),"/sites_AQ_BR.Rds"))
p$id    <- row.names(p)
point   <- terra::vect(p)
point$NMB <- 1:45 - 20 # some values to plot

terra::plot(BR, main = 'add points',xlim = c(-52,-37),ylim = c(-25,-18))
terra::lines(BR)
terra::lines(sp, col = 'gray')
overlay(point,point$NMB,cex = 1.4, add = TRUE)

overlay(point,point$NMB,cex = 1.4, add = FALSE, main = 'new plot')
terra::lines(BR)
terra::lines(sp, col = 'gray')
```

plot_diff*Plot the difference from two SpatRaster objects***Description**Custom difference ($x - y$) plots for SpatRaster object (based on terra package)**Usage**

```
plot_diff(
  x,
  y,
  col,
  absolute = TRUE,
  relative = TRUE,
  lim_1 = NA,
  lim_2 = NA,
  unit = c(units(x), expression("%")),
  ...
)
```

Arguments

x	SpatVector points
y	values to plot
col	color
absolute	to plot absolute difference
relative	to plot relative difference
lim_1	range of values for scale
lim_2	calculate symmetrical scale
unit	annotation for units
...	arguments to be passing to plot_raster

Value

No return value

Examples

```
folder <- system.file("extdata", package="eva3dm")
wrf    <- paste0(folder, "/wrfinput_d01")
A      <- wrf_rast(wrf, 'XLAT')
terra::units(A) <- 'degrees'
B      <- wrf_rast(wrf, 'XLONG')
plot_diff(A,B,int = 2)
```

plot_rast	<i>Plot raster (SpatRaster) object</i>
-----------	--

Description

Custon plot for SpatRaster (terra R-package) object based on terra package

Usage

```
plot_rast(  
  r,  
  color,  
  ncolor = 21,  
  proj = FALSE,  
  plg = list(tic = "none", shrink = 1),  
  pax = list(),  
  latitude = TRUE,  
  longitude = TRUE,  
  int = 10,  
  grid = FALSE,  
  grid_int = int,  
  grid_col = "#666666",  
  add_range = FALSE,  
  ndig = 2,  
  log = FALSE,  
  range,  
  min = -3,  
  max,  
  unit,  
  ...  
)
```

Arguments

r	raster
color	color scale, or name of a custom color scale (see notes)
ncolor	number of colors
proj	TRUE to project the raster to lat-lon
plg	list of parameters passed to terra::add_legend
pax	list of parameters passed to graphics::axis
latitude	add a latitude axis
longitude	add a longitude axis
int	interval of latitude and longitude lines
grid	add grid (graticule style)

grid_int	interval of grid lines
grid_col	color for grid lines
add_range	add legend with max, average and min r values
ndig	number of digits for legend_range
log	TRUE to plot in log-scale
range	range of original values to plot
min	minimum log value for log scale (defoul is -3)
max	maximum log value for log scale
unit	title for color bar (defoult is)
...	arguments to be passing to terra::plot

Value

No return value

Note

color scale includes: 'eva3r' (default), 'eva4', 'blues' and 'diff'

Examples

```
wrf <- paste(system.file("extdata", package = "eva3dm"),
             "/wrfinput_d01", sep="")

r <- wrf_rast(file=wrf, name='XLAT')

plot_rast(r)
```

q2rh

Convert absolute humidity to relative humidity
Description

function to convert absolute humidity to relative humidity.

Usage

```
q2rh(q, t = 15, p = 101325)
```

Arguments

q	vector (or data.frame) of absolute humidity (in g/Kg)
t	vector (or data.frame) of temperature (in Celcius)
p	vector (or data.frame) of pressure (in Pa)

Value

vector or data.frame with time and the relative humidity, units are

Note

default values are from standard atmosphere (288.15 K (15C) / 101325 Pa)

if rh and temp arguments are data.frame, both need to have the same number of lines and columns, first column (time column) will be ignored.

Examples

```
# for a single value (or same length vectors)
q2rh(q = 0.0002038, t = 29.3, p = 100800)

# using all data.frames
times <- seq(as.POSIXct('2024-01-01',tz = 'UTC'),
              as.POSIXct('2024-01-02',tz = 'UTC'),
              by = 'hour')[1:5]
q2   <- data.frame(time = times, a = rep(0.0002038,5))
temp <- data.frame(time = times, a = rep(    29.3,5))
pres <- data.frame(time = times, a = rep( 100800,5))
q2rh(q = q2, t = temp, p = pres)

# using data.frame for q and t (p is cte.)
q2rh(q = q2, t = temp, p = 100000)

# using data.frame for q and p (t is cte.)
q2rh(q = q2, t = 26, p = pres)

# using data.frame only for q (p and t are cte.)
q2rh(q = q2, t = 26, p = 100000)
```

rain

conversion of model precipitation to hourly precipitation
Description

function that converts model accumulated precipitation to hourly precipitation.

Usage

```
rain(rainc, rainnc, verbose = TRUE)
```

Arguments

rainc	data.frame or SpatRaster with RAINC variable
rainnc	data.frame or SpatRaster with RAINNC variable
verbose	set TRUE to display additional information

Value

data.frame time and the hourly precipitation or SpatRaster hourly precipitation

Examples

```
times <- seq(as.POSIXct('2024-01-01', tz = 'UTC'),
              as.POSIXct('2024-01-01 04:00:00', tz = 'UTC'),
              by = 'hour')
RNC   <- data.frame(date = times, aa = c(0.149, 0.149, 0.149, 0.149, 0.149))
RNNC  <- data.frame(date = times, aa = c(0.919, 1.0, 1.1, 1.1, 2.919))
rain(rainc = RNC, rainnc = RNNC)
```

rast_to_ncdf

Function to convert/save a SpatRaster array/Netcdf

Description

Conversion of SpatRaster to array and optionally save on a Netcdf File.

Usage

```
rast_to_ncdf(r, file, name, unit = units(r), XY = FALSE, verbose = TRUE)
```

Arguments

<i>r</i>	SpatRaster object
<i>file</i>	Netcdf file name
<i>name</i>	variable name on a Netcdf file
<i>unit</i>	unit of the variable (set to NA to don't change unit)
<i>XY</i>	set to true if MemoryOrder is XY (only if file is missing)
<i>verbose</i>	display additional information

Value

numerical array

Note

eva3dm::wrf_rast support 3d SpatRaster, in case of a 4d variable use other approach to save on file.

Examples

```
folder  <- system.file("extdata", package="eva3dm")
wrf_file <- paste0(folder, "/wrf.day1.o3.nc")

Rast    <- wrf_rast(wrf_file, 'o3')
A       <- rast_to_ncdf(Rast)
```

read_stat	<i>Function to read stats and evaluation</i>
-----------	--

Description

Function to read stats and evaluation output

Usage

```
read_stat(file, sep = ";", dec = ".", verbose = FALSE, ...)
```

Arguments

file	model data.frame
sep	the field separator string, passed to read.table function
dec	the string to use for decimal points, passed to read.table function
verbose	display additional information
...	arguments passed to read.table functions

Value

No return value

Examples

```
sample <- read_stat(file = paste0(system.file("extdata", package = "eva3dm"), "/sample.txt"),
                      verbose = TRUE)

sample <- read_stat(file = paste0(system.file("extdata", package = "eva3dm"), "/sample.csv"),
                      verbose = TRUE)
```

rh2q	<i>Convert relative humidity to absolute humidity</i>
------	---

Description

function to convert humidity to absolute humidity using Tetens formula, assuming standard atmosphere conditions.

Usage

```
rh2q(rh, temp = 15)
```

Arguments

<code>rh</code>	vector (or data.frame) of relative humidity (in percentage)
<code>temp</code>	vector (or data.frame) of temperature (in Celsius)

Value

value of data.frame with time and the absolute humidity, units are g/g

Note

default values are from standard atmosphere (288.15 K / 15 C)

if rh and temp arguments are data.frame, both need to have the same number of lines and columns, first column (time column) will be ignored.

Examples

```
# for a singfle value
rh2q(rh = 99, temp = 25)

# vector of rh values
rh2q(rh = c(0,seq(1,100, by = 4)), temp = 25)

# vector of values for rh and temp
rh2q(rh = c(0,seq(1,100, by = 4)), temp = 10:35)

# rh is data.frame and temp is a value
times <- seq(as.POSIXct('2024-01-01',tz = 'UTC'),
              as.POSIXct('2024-01-02',tz = 'UTC'),
              by = 'hour')
rh2q(rh = data.frame(time = times, a = seq(1,100, by = 4)),temp = 25)

# using both rh and temp are data.frames
rh2q(rh = data.frame(time = times, a = seq(1,100, by = 4)),
      temp = data.frame(time = times, a = 11:35))
```

Description

functions to evaluate the spatial performance using satellite

Usage

```
sat(
  mo,
  ob,
  rname,
```

```

    table = NULL,
    n = 6,
    min = NA,
    max = NA,
    method = "bilinear",
    eval_function = stat,
    mask,
    verbose = TRUE,
    ...
)

```

Arguments

mo	SpatRaster or raster with model
ob	SpatRaster or raster with observations
rname	passed to stat
table	data.frame to append the results
n	number of points from the boundary removed, default is 5
min	minimum value cutoff
max	maximum value cutoff
method	passed to terra::resample
eval_function	evaluation function (default is stat)
mask	optional SpatVector to mask the results
verbose	set TRUE to display additional information
...	other arguments passed to stat

Value

a data.frame

Note

If a YOU DIED error message appears, means you are removing all the valid values using the arguments min or max.

If cate() is used for eval_function, the argument threshold must be included (see example).

Examples

```

model_o3 <- terra::rast(paste0(system.file("extdata", package="eva3dm"),
                                "/camx_no2.Rds"))
omi_o3   <- terra::rast(paste0(system.file("extdata", package="eva3dm"),
                                "/omi_no2.Rds"))

# generate the statistical indexes
sat(mo = model_o3, ob = omi_o3, rname = 'NO2_statistical')

```

```
# generate categorical evaluation using 3.0 as threshold
sat(mo = model_o3, ob = omi_o3, rname = 'NO2_categorical',
    eval_function = cate, threshold = 3.0)
```

stat*Calculate evaluation statistics from numerical vectors***Description**

Calculate statistical indexes (Number of pairs, observation average, model average, correlation, Index Of Agreement, Factor of 2, Root Mean Square Error, Mean Bias, Mean error, Normalized Mean Bias, and Normalized Mean Bias) for model evaluation

Usage

```
stat(
  model,
  observation,
  wd = FALSE,
  cutoff = NA,
  cutoff_NME = NA,
  nobs = 8,
  rname,
  verbose = TRUE
)
```

Arguments

<code>model</code>	numeric vector with paired model data
<code>observation</code>	numeric vector with paired observation data
<code>wd</code>	logical, set true to apply a rotation on wind direction, see notes
<code>cutoff</code>	(optionally the maximum) valid value for observation
<code>cutoff_NME</code>	(optionally the maximum) valid value for observation for NME, MFB and MFE
<code>nobs</code>	minimum number of observations
<code>rname</code>	row name
<code>verbose</code>	display additional information

Value

`data.frame` with calculated Number of pairs, observation average, model average, correlation, Index Of Agreement, Factor of 2, Root Mean Square Error, Mean Bias, Mean error, Normalized Mean Bias, and Normalized Mean Bias

Note

the option wd = TRUE applies a rotation of 360 on model wind direction to minimize the angular difference.

References

- Emery, C. and Tai., E. 2001. Enhanced Meteorological Modeling and Performance Evaluation for Two Texas Ozone Episodes.
- Monk, K. et al. 2019. Evaluation of Regional Air Quality Models over Sydney and Australia: Part 1—Meteorological Model Comparison. *Atmosphere* 10(7), p. 374. doi: 10.3390/atmos10070374.
- Ramboll. 2018. PacWest Newport Meteorological Performance Evaluation.
- Zhang, Y. et al. 2019. Multiscale Applications of Two Online-Coupled Meteorology-Chemistry Models during Recent Field Campaigns in Australia, Part I: Model Description and WRF/Chem-ROMS Evaluation Using Surface and Satellite Data and Sensitivity to Spatial Grid Resolutions. *Atmosphere* 10(4), p. 189. doi: 10.3390/atmos10040189.
- Emery, C., Liu, Z., Russell, A.G., Odman, M.T., Yarwood, G. and Kumar, N. 2017. Recommendations on statistics and benchmarks to assess photochemical model performance. *Journal of the Air & Waste Management Association* 67(5), pp. 582–598. doi: 10.1080/10962247.2016.1265027.
- Zhai, H., Huang, L., Emery, C., Zhang, X., Wang, Y., Yarwood, G., ... & Li, L. (2024). Recommendations on benchmarks for photochemical air quality model applications in China—NO₂, SO₂, CO and PM10. *Atmospheric Environment*, 319, 120290.

Examples

```
model <- 1:100
data <- model + rnorm(100,0.2)
stat(model = model, observation = data)
```

Description

Create templates of code (r-scripts and bash job-submission script) to read, post-process and evaluate model results.

Usage

```
template(
  root,
  template = "WRF",
  case = "case",
  env = "rspatial",
  scheduler = "SBATCH",
```

```

partition = "main",
project = "PROJECT",
verbose = TRUE
)

```

Arguments

root	directory to create the template
template	template type (see notes)
case	case to be evaluated
env	name of the conda environment
scheduler	job scheduler used (SBATCH or PBS)
partition	partition name
project	project name
verbose	display additional information

Value

no value returned, create folders and other template scripts

Note

Templates types available:

- WRF (model post-process for METAR + INMET)
- WRF-Chem (model post-process for METAR, AQS in Brazil and AERONET)
- EXP (model post-process for one experimental site including PBL variables)
- METAR (download observations)
- MET (evaluation of meteorology)
- AQ (evaluation of air quality)
- PSA (model post-processing with CDO for satellite evaluation)
- SAT (evaluation of precipitation using GPCP satellite)

Examples

```

temp <- file.path(tempdir(),"POST")
template(root = temp,template = 'WRF', case = 'WRF-only')

```

Description

Function to calculate model wind direction

Usage

```
uv2wd(u, v, verbose = TRUE)
```

Arguments

u	data.frame with model time-series of U10
v	data.frame with model time-series of V10
verbose	display additional information

Value

vector or data.frame with time and the wind direction, units are degree north

Examples

```
times <- seq(as.POSIXct('2024-01-01',tz = 'UTC'),
              as.POSIXct('2024-01-02',tz = 'UTC'),
              by = 'hour')
U10 = data.frame(times = times,
                  test1 = c(3.29,2.07,1.96,2.82,3.73,
                           4.11,4.96,6.33,7.39,7.59,
                           7.51,7.22,6.81,6.43,5.81,
                           4.02,3.03,2.68,2.40,2.20,
                           2.09,1.95,1.66,1.39,1.4),
                  test2 = c(6.29,4.87,6.16,7.12,8.77,
                           10.16,10.85,11.45,11.21,11.04,
                           11.09,10.67,10.48,10.00,8.96,
                           6.36,5.62,5.83,5.83,5.25,
                           4.11,3.08,2.26,1.14,-0.10))
V10 = data.frame(times = times,
                  test1 = c(-8.87,-4.23,-2.81,-2.59,-4.58,
                           -4.80,-5.33,-5.86,-6.12,-6.13,
                           -6.11,-5.76,-5.91,-5.60,-5.09,
                           -3.33,-2.50,-2.29,-2.14,-2.07,
                           -1.95,-1.97,-2.04,-2.03,-1.9),
                  test2 = c(11.80,5.88,5.74,5.56,6.87,
                           8.39,8.68,8.33,7.90,7.42,
                           6.96,6.87,6.36,5.61,5.16,
                           4.16,4.25,4.59,4.51,3.90,
                           2.97,1.98,1.04,-0.08,-0.44))
uv2wd(u = U10, v = V10)
```

uv2ws

Function to calculate model wind speed

Description

Function to calculate model wind speed

Usage

```
uv2ws(u, v, verbose = TRUE)
```

Arguments

<code>u</code>	data.frame with model time-series of U10
<code>v</code>	data.frame with model time-series of V10
<code>verbose</code>	display additional information

Value

vector or data.frame with time and the wind sped, units are m/s

Examples

```
uv2ws(u = U10, v = V10)
```

vars*Function to return variable names*

Description

Return variable names of a NetCDF

Usage

```
vars(file = NA, action = "get", verbose = FALSE)
```

Arguments

file	file name
action	'get' to return variable names or 'print' to print
verbose	display additional information

Value

string

Examples

```
vars(paste0(system.file("extdata", package="eva3dm"), '/wrfinput_d01'))
```

wrf_rast*Creates SpatRaster object from wrf file*

Description

Creates a SpatRaster (terra R-package) object from a variable from wrf file (or another compatible NetCDF)

Usage

```
wrf_rast(
  file = file.choose(),
  name = NA,
  map,
  level = 1,
  times,
  latlon = FALSE,
  method = "bilinear",
  as_polygons = FALSE,
  flip_h = FALSE,
  flip_v = FALSE,
  verbose = FALSE,
  ...
)
```

Arguments

file	wrf file
name	variable name
map	(optional) file with lat-lon variables and grid information
level	only for 4d data, numeric, default is 1 for surface (include all times)
times	only for 4d data, numeric, set to select time instead of levels (include all levels)
latlon	logical (default is FALSE), set TRUE project the output to "+proj=longlat +datum=WGS84 +no_defs"
method	method passed to terra::projection, default is bilinear
as_polygons	logical, true to return a SpatVector instead of SpatRaster
flip_h	horizontal flip (by rows)
flip_v	vertical flip (by cols)
verbose	display additional information
...	extra arguments passed to ncdf4::ncvar_get

Value

SpatRaster object (terra package)

Examples

```
{
  wrf <- paste(system.file("extdata", package = "eva3dm"),
               "/wrfinput_d01", sep="")
  r <- wrf_rast(file=wrf, name='XLAT')
  plot_rast(r)
}
```

write_stat*Functions to write stats and evaluation*

Description

Functions to write the output from evaluation functions. If the file name ends with .csv the function write.csv is used otherwise the function write.table is used.

Usage

```
write_stat(stat, file, sep = ";", dec = ".", verbose = FALSE, ...)
```

Arguments

stat	observed data.frame
file	model data.frame
sep	the field separator string, passed to write.table function
dec	he string to use for decimal points, passed to write.table function
verbose	display additional information
...	arguments passed to write.table and write.csv functions

Value

No return value

Examples

```
sample <- read_stat(paste0(system.file("extdata", package = "eva3dm"), "/sample.csv"),
                      verbose = TRUE)
dir.create(file.path(tempdir(), "stats"))

write_stat(file    = paste0(file.path(tempdir(), "stats"), '/sample.txt'),
           stat    = sample,
           verbose = TRUE)

write_stat(file    = paste0(file.path(tempdir(), "stats"), '/sample.csv'),
           stat    = sample,
           verbose = TRUE)
```

<code>%IN%</code>	<i>Returns the common columns</i>
-------------------	-----------------------------------

Description

results of 'd01 in d02' style syntax

Usage

```
x %IN% y
```

Arguments

<code>x</code>	data.frame
<code>y</code>	data.frame or character string

Value

data.frame with common columns or a cropped SpatRaster

Note

a message is always displayed to keep easy to track and debug issues (with the results and the evaluation process).

can be used to crop rast objects, such as arguments of sat() function

Examples

```
times <- seq(as.POSIXct('2024-01-01',tz = 'UTC'),
              as.POSIXct('2024-01-02',tz = 'UTC'),
              by = 'hour')
random_stuff <- rnorm(25,10)

observation <- data.frame(date = times,
                           site_1 = random_stuff,
                           site_3 = random_stuff,
                           site_4 = random_stuff,
                           site_5 = random_stuff,
                           site_6 = random_stuff,
                           site_7 = random_stuff)

model_d01 <- data.frame(date = times,
                         site_1=random_stuff+1,
                         site_2=random_stuff+2,
                         site_3=random_stuff+3,
                         site_4=random_stuff+4)

model_d02 <- data.frame(date = times,
                         site_1=random_stuff-1,
```

```

site_3=randon_stuff-3)

# multiline
model_d01_in_d02 <- model_d01 %IN% model_d02
eva(mo = model_d01_in_d02, ob = observation, rname = 'd01 in d02')

# or single line
eva(mo = model_d01 %IN% model_d02, ob = observation, rname = 'd01 in d02')
# or
eva(mo = model_d01, ob = observation %IN% model_d02, rname = 'd01 in d02')

```

%at%

*Combine stats and site list to overlay plot***Description**

combines the stats (from individual station evaluation) and site list in a SpatVector using row.names

Usage

```
stat %at% site
```

Arguments

stat	data.frame with stats or other variable (containing row.names and other variables)
site	data.frame with site list (containing row.names, lat and lon)

Value

SpatVector (terra package)

Examples

```

sites<- readRDS(paste0(system.file("extdata",package="eva3dm"),"/sites_AQ_BR.Rds"))
model<- readRDS(paste0(system.file("extdata",package="eva3dm"),"/model.Rds"))
obs  <- readRDS(paste0(system.file("extdata",package="eva3dm"),"/obs.Rds"))

stats <- eva(mo = model, ob = obs, site = 'Americana')
stats <- eva(mo = model, ob = obs, site = 'SAndre',table = stats)
stats <- eva(mo = model, ob = obs, site = 'VVIBes',table = stats)

print(stats)

geo_stats <- stats %at% sites

print(geo_stats)

```

Index

%IN%, 36
%at%, 37

atr, 2
cate, 3, 7
daily, 5

eva, 6
extract_max_8h, 8
extract_mean, 9
extract_serie, 10

get_distances, 12

hourly, 12

interp, 14

legend_range, 15

ma8h, 16
mda8, 17

ncdump, 18

overlay, 18

plot_diff, 20
plot_rast, 21

q2rh, 22

rain, 23
rast_to_netcdf, 24
read_stat, 25
rh2q, 25

sat, 26
stat, 7, 28

template, 29

uv2wd, 30
uv2ws, 32

vars, 33

wrf_rast, 33
write_stat, 35