

Package ‘lsoda’

April 24, 2025

Type Package

Title 'C++' Header Library for Ordinary Differential Equations

Version 1.1

Description A 'C++' header library for using the 'libsoda-cxx' library with R. The 'C++' header reimplements the 'lsoda' function from the 'ODEPACK' library for solving initial value problems for first order ordinary differential equations (Hindmarsh, 1982; <https://computing.llnl.gov/sites/default/files/ODEPACK_pub1_u88007.pdf>). The 'C++' header can be used by other R packages by linking against this package. The 'C++' functions can be called inline using 'Rcpp'. Finally, the package provides an 'ode' function to call from R.

License MIT + file LICENSE

URL <https://github.com/mclements/lsoda>

BugReports <https://github.com/mclements/lsoda/issues>

Imports Rcpp (>= 1.0.12)

Suggests deSolve, RcppArmadillo, RcppEigen, microbenchmark

LinkingTo Rcpp

RoxygenNote 7.3.2

Encoding UTF-8

NeedsCompilation yes

Author Mark Clements [aut, cre],

Dilawar Singh [ctb],

Heng Li [ctb],

Peter N. Brown [ctb],

George D. Byrne [ctb],

Alan C. Hindmarsh [ctb],

Cleve Moler [ctb],

Linda R. Petzold [ctb]

Maintainer Mark Clements <mark.clements@ki.se>

Repository CRAN

Date/Publication 2025-04-24 11:40:10 UTC

Contents

<i>ode</i>	2
Index	3

<i>ode</i>	<i>Ordinary differential equation solver using lsoda</i>
------------	--

Description

Ordinary differential equation solver using lsoda

Usage

```
ode(y, times, func, rtol = 1e-06, atol = 1e-06)
```

Arguments

<i>y</i>	vector of initial state values
<i>times</i>	vector of times – including the start time
<i>func</i>	R function with signature <i>function(t,y)</i> that returns a list. The first list element is a vector for <i>dy/dt</i> . The second list elements, if it exists, is a vector of result calculations to be retained.
<i>rtol</i>	double for the relative tolerance
<i>atol</i>	double for the absolute tolerance

Value

a matrix for times in the first column and the state andd results values in the other columns.

Examples

```
times = c(0,0.4*10^(0:10))
y = c(1,0,0)
func = function(t,y,...) {
  ydot = rep(0,3)
  ydot[1] = 1.0E4 * y[2] * y[3] - .04E0 * y[1]
  ydot[3] = 3.0E7 * y[2] * y[2]
  ydot[2] = -1.0 * (ydot[1] + ydot[3])
  list(ydot, sum(y))
}
lsoda::ode(y,times,func, rtol=1e-8, atol=1e-8)
```

Index

ode, [2](#)