

Package ‘m61r’

October 13, 2022

Type Package

Version 0.0.3

Title Package About Data Manipulation in Pure Base R

Description Data manipulation in one package and in base R.

Minimal. No dependencies.

‘dplyr’ and ‘tidyr’-like in one place.

Nothing else than base R to build the package.

Depends R (>= 3.4.4)

License MIT + file LICENSE

URL <https://github.com/pv71u98h1/m61r/>

BugReports <https://github.com/pv71u98h1/m61r/issues/>

Encoding UTF-8

NeedsCompilation no

Author Jean-Marie Lepioufle [aut, cre]

Maintainer Jean-Marie Lepioufle <pv71u98h1@gmail.com>

Repository CRAN

Date/Publication 2022-05-06 15:50:02 UTC

R topics documented:

arrange	2
expression	3
filter	3
group_by	4
join	5
m61r	6
mutate	11
reshape	12
select	14
summarise	15
value	15

arrange	<i>Arrange your data.frames</i>
---------	---------------------------------

Description

Re-arrange your data.frame in ascending or descending order and given one or several columns.

Usage

```
arrange_(df, ...)
desange_(df, ...)
```

Arguments

df	data.frame
...	formula used for arranging the data.frame

Value

The functions return an object of the same type as df. The output has the following properties:
Properties:

- Columns are not modified.
- Output get rows in the order specified by
-
- Data frame attributes are preserved.

Examples

```
tmp <- arrange_(CO2, ~c(conc))
head(tmp)

tmp <- arrange_(CO2, ~c(Treatment, conc, uptake))
head(tmp)

tmp <- desange_(CO2, ~c(Treatment, conc, uptake))
head(tmp)
```

expression	<i>Formula to be run on a data.frame given a group</i>
------------	--

Description

Evaluate a formula on the data.frame.

Usage

```
expression_(df, group=NULL, fun_expr)
```

Arguments

df	data.frame
group	formula that describes the group
fun_expr	formula that describes the expression to be run on the data.frame

Value

The function returns a list. Each element of the list get the result of processed expressions determined in . . . on the whole data frame df if group is kept NULL, or for each group determined in group otherwise. The class of each element is intrinsic to the output of the expression determined in argument . . .

Examples

```
expression_(CO2, fun_expr=~mean(conc))

expression_(CO2, fun_expr=~conc/uptake)

# with group
expression_(CO2, group=~Type, fun_expr=~mean(uptake))

expression_(CO2, group=~Type, fun_expr=~lm(uptake~conc))
```

filter	<i>filter a data.frame</i>
--------	----------------------------

Description

Filter rows of a data.frame with conditions.

Usage

```
filter_(df, subset = NULL)
```

Arguments

<code>df</code>	data.frame
<code>subset</code>	formula that describes the conditions

Value

The function returns an object of the same type as `df`. Properties:

- Columns are not modified.
- Only rows following the condition determined by
- `subset` appear.
- Data frame attributes are preserved.

Examples

```
tmp <- filter_(C02, ~Plant=="Qn1")
head(tmp)

tmp <- filter_(C02, ~Type=="Quebec")
head(tmp)
```

`group_by`*group_by a data.frame by chosen columns***Description**

Group a data.frame by chosen columns

Usage

```
group_by_(df, group = NULL)
```

Arguments

<code>df</code>	data.frame
<code>group</code>	formula that describes the group

Value

The function returns a list. Each element of the list is a subset of data frame `df`. Subset is determined by variables given in `group`. Each data frame get the following properties:

- Columns are not modified.
- Only rows corresponding to the subset.
- Data frame attributes are preserved.

Examples

```
tmp <- group_by_(CO2, ~c(Type, Treatment))

tmp[[1]]
```

join

Join two data.frames

Description

Join two data.frames.

Usage

```
left_join_(df, df2, by = NULL, by.x = NULL, by.y = NULL)

anti_join_(df, df2, by = NULL, by.x = NULL, by.y = NULL)

full_join_(df, df2, by = NULL, by.x = NULL, by.y = NULL)

inner_join_(df, df2, by = NULL, by.x = NULL, by.y = NULL)

right_join_(df, df2, by = NULL, by.x = NULL, by.y = NULL)

semi_join_(df, df2, by = NULL, by.x = NULL, by.y = NULL)
```

Arguments

df	data.frame
df2	data.frame
by	column names of the pivot of both data.frame 1 and data.frame 2 if they are identical. Otherwise, better to use by.x and by.y
by.x	column names of the pivot of data.frame 1
by.y	column names of the pivot of data.frame 2

Value

The functions return a data frame. The output has the following properties:

- For functions `left_join()`, `inner_join()`, `full_join()`, and `right_join()`, output includes all `df1` columns and all `df2` columns. For columns with identical names in `df1` and `df2`, a suffix '`.x`' and '`.y`' is added. For `left_join()`, all `df1` rows with matching rows of `df2`. For `inner_join()`, a subset of `df1` rows matching rows of `df2`. For `full_join()`, all `df1` rows, with all `df2` rows. For `right_join()`, all `df2` rows with matching rows of `df1`.
- For functions `semi_join()` and `anti_join()`, output include columns of `df1` only. For `semi_join()`, all `df1` rows with a match in `df2`. For `anti_join()`, a subset of `df1` rows not matching rows of `df2`.

Examples

```

books <- data.frame(
  name = I(c("Tukey", "Venables", "Tierney", "Ripley",
            "Ripley", "McNeil", "R Core")),
  title = c("Exploratory Data Analysis",
            "Modern Applied Statistics ...",
            "LISP-STAT",
            "Spatial Statistics", "Stochastic Simulation",
            "Interactive Data Analysis",
            "An Introduction to R"),
  other.author = c(NA, "Ripley", NA, NA, NA, NA, "Venables & Smith"))

authors <- data.frame(
  surname = I(c("Tukey", "Venables", "Tierney", "Ripley", "McNeil", "Asimov")),
  nationality = c("US", "Australia", "US", "UK", "Australia", "US"),
  deceased = c("yes", rep("no", 4), "yes"))

tmp <- left_join_(books, authors, by.x = "name", by.y = "surname")
head(tmp)

tmp <- inner_join_(books, authors, by.x = "name", by.y = "surname")
head(tmp)

tmp <- full_join_(books, authors, by.x = "name", by.y = "surname")
head(tmp)

tmp <- right_join_(books, authors, by.x = "name", by.y = "surname")
head(tmp)

tmp <- semi_join_(books, authors, by.x = "name", by.y = "surname")
head(tmp)

tmp <- anti_join_(books, authors, by.x = "name", by.y = "surname")
head(tmp)

```

m6lr

Create m6lr object

Description

Create a m6lr object that enables to run a sequence of operations on a data.frame.

Usage

```
m6lr(df = NULL)

## S3 method for class 'm6lr'
x[i, j, ...]
```

```

## S3 replacement method for class 'm61r'
x[i, j] <- value

## S3 method for class 'm61r'
print(x, ...)

## S3 method for class 'm61r'
names(x, ...)

## S3 method for class 'm61r'
dim(x, ...)

## S3 method for class 'm61r'
as.data.frame(x, ...)

## S3 method for class 'm61r'
rbind(x, ...)

## S3 method for class 'm61r'
cbind(x, ...)

```

Arguments

df	data.frame
x	object of class m61r
i	row
j	column
...	further arguments passed to or from other methods
value	value to be assigned

Value

The function `m61r` returns an object of type `m61r`.

Argument `df` get stored internally to the object `m61r`. One manipulates the internal `data.frame` by using internal functions similar to the ones implemented in package `m61r` for `data.frames` as `arrange`, `desolve`, `filter`, `join` and its relatives, `mutate` and `transmute`, `gather` and `spread`, `select`, `group_by`, `summarise`, `values` and `modify`. The result of the last action is stored internally to the object `m61r` until the internal function `values` get called. It is thus possible to create a readable sequence of actions on a `data.frame`.

In addition,

- `[.m61r` returns a subset of the internal `data.frame` embedded to the object `m61r`.
- `[<- .m61r` assigns `value` to the internal `data.frame` embedded to the object `m61r`.
- `print.m61r` prints the internal `data.frame` embedded to the object `m61r`.

- `names.m61r` provides the names of the column of the internal `data.frame` embedded to the object `m61r`.
- `dim.m61r` provides the dimensions of the internal `data.frame` embedded to the object `m61r`.
- `as.data.frame.m61r` extracts the internal `data.frame` embedded to the object `m61r`.
- `cbind.m61r` combines by `_c_olumns` two objects `m61r`.
- `rbind.m61r` combines by `_r_ows` two objects `m61r`.
- `left_join`, `anti_join`, `full_join`, `inner_join`, `right_join`, `semi_join` join two objects `m61r`.

Finally, it is possible to clone a `m61r` object into a new one by using the internal function `clone`.

Examples

```
# init
co2 <- m61r(df=C02)

# filter
co2$filter(~Plant=="Qn1")
co2

co2$filter(~Type=="Quebec")
co2

# select
co2$select(~Type)
co2

co2$select(~c(Plant,Type))
co2

co2$select(--Type)
co2

co2$select(variable=~~(Plant:Treatment))
co2

# mutate/transmute
co2$mutate(z=~conc/uptake)
co2

co2$mutate(mean=~mean(uptake))
co2

co2$mutate(z1=~uptake/conc,y=~conc/100)
co2

co2$transmute(z2=~uptake/conc,y2=~conc/100)
co2

# summarise
```

```

co2$summarise(mean=mean(uptake),sd=sd(uptake))
co2

co2$group_by(~c(Type,Treatment))
co2$summarise(mean=mean(uptake),sd=sd(uptake))
co2

# arrange/dessange
co2$arrange(~c(conc))
co2

co2$arrange(~c(Treatment,conc,uptake))
co2

co2$desange(~c(Treatment,conc,uptake))
co2

# join
authors <- data.frame(
  surname = I(c("Tukey", "Venables", "Tierney", "Ripley", "McNeil")),
  nationality = c("US", "Australia", "US", "UK", "Australia"),
  deceased = c("yes", rep("no", 4)))

books <- data.frame(
  name = I(c("Tukey", "Venables", "Tierney", "Ripley",
             "Ripley", "McNeil", "R Core")),
  title = c("Exploratory Data Analysis",
            "Modern Applied Statistics ...",
            "LISP-STAT",
            "Spatial Statistics", "Stochastic Simulation",
            "Interactive Data Analysis",
            "An Introduction to R"),
  other.author = c(NA, "Ripley", NA, NA, NA, NA,"Venables & Smith"))

## inner join
tmp <- m6lr(df=authors)

tmp$inner_join(books, by.x = "surname", by.y = "name")
tmp

## left join
tmp$left_join(books, by.x = "surname", by.y = "name")
tmp

## right join
tmp$right_join(books, by.x = "surname", by.y = "name")
tmp

## full join
tmp$full_join(books, by.x = "surname", by.y = "name")
tmp

## semi join

```

```

tmp$semi_join(books, by.x = "surname", by.y = "name")
tmp

## anti join #1
tmp$anti_join(books, by.x = "surname", by.y = "name")
tmp

## anti join #2
tmp2 <- m61r(df=books)
tmp2$anti_join(authors, by.x = "name", by.y = "surname")
tmp2

## with two m61r objects
tmp1 <- m61r(books)
tmp2 <- m61r(authors)
tmp3 <- anti_join(tmp1,tmp2, by.x = "name", by.y = "surname")
tmp3

# Reshape

## gather
df3 <- data.frame(id = 1:4,
                    age = c(40,50,60,50),
                    dose.a1 = c(1,2,1,2),
                    dose.a2 = c(2,1,2,1),
                    dose.a14 = c(3,3,3,3))

df4 <- m61r::m61r(df3)
df4$gather(pivot = c("id","age"))
df4

## spread
df3 <- data.frame(id = 1:4,
                    age = c(40,50,60,50),
                    dose.a1 = c(1,2,1,2),
                    dose.a2 = c(2,1,2,1),
                    dose.a14 = c(3,3,3,3))

df4 <- m61r::gather_(df3,pivot = c("id","age"))
df4 <- rbind(df4,
             data.frame(id=5, age=20,parameters="dose.a14",values=8),
             data.frame(id=6, age=10,parameters="dose.a1",values=5))

tmp <- m61r::m61r(df4)
tmp$spread(col_name="parameters",col_values="values",pivot=c("id","age"))
tmp

# equivalence
co2      # is not equivalent to co2[]
co2[]    # is equivalent to co2$values()
co2[1,]  # is equivalent to co2$values(1,)
co2[,2:3] # is equivalent to co2$values(,2:3)

```

```
co2[1:10,1:3] # is equivalent to co2$values(1:10,2:3)
co2[1,"Plant"]# is equivalent to co2$values(1,"Plant")

# modification on m61r object only stay for one step
co2[1,"conc"] <- 100
co2[1,] # temporary result
co2[1,] # back to normal

# WARNING:
# Keep the brackets to manipulate the intern data.frame
co2[] <- co2[-1,]
co2[1:3,] # temporary result
co2[1:3,] # back to normal

# ... OR you will destroy co2, and only keep the data.frame
# co2 <- co2[-1,]
# class(co2) # data.frame

# descriptive manipulation
names(co2)
dim(co2)
str(co2)

## cloning
# The following will only create a second variable that point on
# the same object (!= cloning)
foo <- co2
str(co2)
str(foo)

# Instead, cloning into a new environemnt
foo <- co2$clone()
str(co2)
str(foo)
```

mutate

Mutate and transmute a data.frame

Description

Mutate and transmute a data.frame.

Usage

```
mutate_(df, ...)
```

```
transmute_(df, ...)
```

Arguments

df	data.frame
...	formula used for mutating/transmutating the data.frame

Value

The functions return a data frame. The output has the following properties:

- For function `mutate_()`, output includes all df columns. In addition, new columns are created according to argument ... and placed after the others.
- For function `transmute_()`, output includes only columns created according to argument ... and placed after the others.

Examples

```
tmp <- mutate_(CO2,z=~conc/uptake)
head(tmp)

# Return an warning: expression mean(uptake) get a result with 'nrow' different from 'df'
# tmp <- mutate_(CO2,mean=~mean(uptake))

tmp <- mutate_(CO2,z1=~uptake/conc,y=~conc/100)
head(tmp)

tmp <- transmute_(CO2,z2=~uptake/conc,y2=~conc/100)
head(tmp)
```

reshape

Reshape a data.frame

Description

Reshape a data.frame.

Usage

```
gather_(df, new_col_name = "parameters", new_col_values = "values",
       pivot)

spread_(df, col_name, col_values, pivot)
```

Arguments

df	data.frame
new_col_name	name of the new column 'parameters'
new_col_values	name of the new columns 'values'
col_name	name of the column 'parameters'
col_values	name of the new columns 'values'
pivot	name of the columns used as pivot

Details

A data frame is said 'wide' if several of its columns describe connected information of the same record. A data frame is said 'long' if two of its columns provide information about records, with one describing their name and the second their value. Functions `gather_()` and `spread_()` enable to reshape a data frames from a 'wide' format to a 'long' format, and vice-versa.

Value

The functions return a data frame.

- Output from function `gather_()` get 'pivot' columns determined by argument `pivot`, and 'long' columns named according to arguments `new_col_name` and `new_col_values`.
- Output from function `spread_()` get 'pivot' columns determined by argument `pivot`, and 'wide' columns named according to values in column determined by argument `col_name`. For 'wide' columns, each row corresponds to values present in column determined by argument `col_values`.

Examples

```
df3 <- data.frame(id = 1:4,
                    age = c(40,50,60,50),
                    dose.a1 = c(1,2,1,2),
                    dose.a2 = c(2,1,2,1),
                    dose.a14 = c(3,3,3,3))

gather_(df3,pivot = c("id","age"))

df4 <- gather_(df3,pivot = c("id","age"))
df5 <- rbind(df4,
             data.frame(id=5, age=20,parameters="dose.a14",values=8),
             data.frame(id=6, age=10,parameters="dose.a1",values=5))

spread_(df5,col_name="parameters",col_values="values",pivot=c("id","age"))
```

<code>select</code>	<i>select columns of a data.frame</i>
---------------------	---------------------------------------

Description

Select columns of a data.frame.

Usage

```
select_(df, variable = NULL)
```

Arguments

<code>df</code>	<code>data.frame</code>
<code>variable</code>	formula that describes the selection

Value

`select_()` returns a data frame. Properties:

- Only columns following the condition determined by
- `variable` appear.
- Rows are not modified.

Examples

```
tmp <- select_(CO2, ~Type)
head(tmp)

tmp <- select_(CO2, ~c(Plant, Type))
head(tmp)

tmp <- select_(CO2, ~-Type)
head(tmp)

tmp <- select_(CO2, variable = ~-(Plant:Treatment))
head(tmp)
```

summarise	<i>Summarise formula on groups</i>
-----------	------------------------------------

Description

Summarise formulas on a data.frame.

Usage

```
summarise_(df, group = NULL, ...)
```

Arguments

df	data.frame
group	formula that describes the group
...	formulas to be generated

Value

summarise_() returns a data frame. If argument group is not NULL, output get its first columns called according to the names present in argument group. The following columns are called according to the name of each argument present in Each row corresponds to processed expressions determined in ... for each group determined in group, or over the whole data frame if group is NULL.

Examples

```
summarise_(CO2, a=~mean(uptake), b=~sd(uptake))  
summarise_(CO2, group=~c(Type, Treatment), a=~mean(uptake), b=~sd(uptake))
```

value	<i>get or assign a value to a data.frame</i>
-------	--

Description

Get or assign a value to a data.frame

Usage

```
value_(df, i, j)  
'modify_<-'(df, i, j, value)
```

Arguments

df	data.frame
i	row
j	column
value	value to be assigned

Value

The functions `value_` and '`modify_<-`' return a data frame. Properties:

- Only rows determined by
- i appear. If
- i is missing, no row is filtered.
- Only columns determined by
- j appear. If
- j is missing, no column is filtered.

Besides,

- For function `value_`: If argument i is non-missing and argument j is missing, the function returns an object of the same type as df. If both arguments i and j are missing, the function returns an object of the same type as df.
- For function '`modify_<-`

Examples

```

tmp <- value_(CO2,1,2)
attributes(tmp) # data frame

tmp <- value_(CO2,1:2,2)
attributes(tmp) # data frame

tmp <- value_(CO2,1:2,2:4)
attributes(tmp) # data frame

tmp <- value_(CO2,,2)
attributes(tmp) # data frame

tmp <- value_(CO2,2)
attributes(tmp) # same as CO2

tmp <- value_(CO2)
attributes(tmp) # same as CO2

df3 <- data.frame(id = 1:4,
                   age = c(40,50,60,50),
                   dose.a1 = c(1,2,1,2),
                   dose.a2 = c(2,1,2,1),

```

```
dose.a14 = c(3,3,3,3))  
  
'modify_<-'(df3,1,2,6)  
  
'modify_<-'(df3,1:3,2:4,data.frame(c(20,10,90),c(9,3,4),c(0,0,0)))
```

Index

* **m61r**
 arrange, 2
 expression, 3
 filter, 3
 group_by, 4
 join, 5
 m61r, 6
 mutate, 11
 reshape, 12
 select, 14
 summarise, 15
 value, 15
 [.m61r (m61r), 6
 [<-.m61r (m61r), 6
 anti_join (m61r), 6
 anti_join_ (join), 5
 arrange, 2
 arrange_ (arrange), 2
 as.data.frame.m61r (m61r), 6
 cbind.m61r (m61r), 6
 desange_ (arrange), 2
 dim.m61r (m61r), 6
 expression, 3
 expression_ (expression), 3
 filter, 3
 filter_ (filter), 3
 full_join (m61r), 6
 full_join_ (join), 5
 gather_ (reshape), 12
 group_by, 4
 group_by_ (group_by), 4
 inner_join (m61r), 6
 inner_join_ (join), 5
 join, 5
 left_join (m61r), 6
 left_join_ (join), 5
 m61r, 6
 modify_<- (value), 15
 mutate, 11
 mutate_ (mutate), 11
 names.m61r (m61r), 6
 print.m61r (m61r), 6
 rbind.m61r (m61r), 6
 reshape, 12
 right_join (m61r), 6
 right_join_ (join), 5
 select, 14
 select_ (select), 14
 semi_join (m61r), 6
 semi_join_ (join), 5
 spread_ (reshape), 12
 summarise, 15
 summarise_ (summarise), 15
 transmute_ (mutate), 11
 value, 15
 value_ (value), 15