

Package ‘gjam’

October 28, 2025

Type Package

Title Generalized Joint Attribute Modeling

Version 2.7

Date 2025-10-27

Maintainer James S. Clark <jimclark@duke.edu>

Description Analyzes joint attribute data (e.g., species abundance) that are combinations of continuous and discrete data with Gibbs sampling. Full model and computation details are described in Clark et al. (2018) <[doi:10.1002/ecm.1241](https://doi.org/10.1002/ecm.1241)>.

License GPL (>= 2)

Imports Rcpp (>= 0.11.5), MASS, RANN

Depends R (>= 2.10)

LinkingTo Rcpp, RcppArmadillo

Suggests knitr

VignetteBuilder knitr

NeedsCompilation yes

Author James S. Clark [aut, cre],
Daniel Taylor-Rodriquez [aut]

Repository CRAN

Date/Publication 2025-10-28 20:40:02 UTC

Contents

gjam-package	2
gjam	4
gjamCensorY	7
gjamConditionalParameters	9
gjamDeZero	11
gjamFillMissingTimes	12
gjamIIE	14
gjamIIEplot	15
gjamOrdination	17

gjamPlot	18
gjamPoints2Grid	20
gjamPredict	22
gjamPriorTemplate	25
gjamReZero	27
gjamSensitivity	28
gjamSimData	29
gjamSpec2Trait	32
gjamTrimY	33
Index	36

gjam-package	<i>Generalized Joint Attribute Modeling</i>
--------------	---

Description

Analysis of jointly distributed responses that are combinations of continous and discrete data.

Details

Package:	gjam
Type:	Package
Version:	2.7
Date:	2025-10-27
License:	GPL (≥ 2)
LazyLoad:	yes

The generalized joint attribute model (gjam) analyzes multivariate data that are combinations of presence-absence, ordinal, continuous, discrete, composition, zero-inflated, and censored. It does so as a joint distribution over response variables. gjam provides inference on sensitivity to input variables, correlations between responses on the data scale, model selection, and prediction.

Importantly, analysis is done on the observation scale. That is, coefficients and covariances are interpreted on the same scale as the data. Contrast this approach with standard Generalized Linear Models, where coefficients and covariances are difficult to interpret and cannot be compared across responses that are modeled on different scales.

gjam was motivated by species distribution and abundance data in ecology, but can provide an attractive alternative to traditional methods wherever observations are multivariate and combine multiple scales and mixtures of continuous and discrete data.

gjam can be used to model ecological trait data, where species traits are translated to locations as community-weighted means and modes.

Posterior simulation is done by Gibbs sampling. Analysis is done by these functions, roughly in order of how frequently they might be used:

[gjam](#) fits model with Gibbs sampling.

[gjamSimData](#) simulates data for analysis by gjam.
[gjamPriorTemplate](#) sets up prior distribution for coefficients.
[gjamSensitivity](#) evaluates sensitivity to predictors from gjam.
[gjamCensorY](#) defines censored values and intervals.
[gjamTrimY](#) trims the response matrix and aggregates rare types.
[gjamPlot](#) plots output from gjam.
[gjamSpec2Trait](#) constructs plot by trait matrix.
[gjamPredict](#) does conditional prediction.
[gjamConditionalParameters](#) obtains the conditional coefficient matrices.
[gjamOrdination](#) ordinales the response matrix.
[gjamDeZero](#) de-zeros response matrix for storage.
[gjamReZero](#) recovers response matrix from de-zeroed format.
[gjamIIE](#) evaluates indirect effects and interactions.
[gjamIIEplot](#) plots indirect effects and interactions.
[gjamSpec2Trait](#) generates trait values.
[gjamPoints2Grid](#) aggregates incidence data to counts on a lattice.

Author(s)

Author: James S Clark, <jimclark@duke.edu>, Daniel Taylor-Rodriguez

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

Taylor-Rodriguez, D., K. Kaufeld, E. M. Schliep, J. S. Clark, and A. E. Gelfand. 2016. Joint species distribution modeling: dimension reduction using Dirichlet processes. *Bayesian Analysis*, 12, 939-967. doi: 10.1214/16-BA1031.

See Also

[gjam](#), [gjamSimData](#), [gjamPriorTemplate](#), [gjamSensitivity](#), [gjamCensorY](#), [gjamTrimY](#), [gjamPredict](#),
[gjamSpec2Trait](#), [gjamPlot](#), [gjamPredict](#), [gjamConditionalParameters](#), [gjamDeZero](#), [gjamReZero](#)

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

gjam

*Generalized Joint Attribute Modeling***Description**

Analyzes joint attribute data (e.g., species abundance) with Gibbs sampling. Input can be output from [gjamSimData](#). Returns a list of objects from Gibbs sampling that can be plotted by [gjamPlot](#).

Usage

```
gjam(formula, xdata, ydata, modelList)

## S3 method for class 'gjam'
print(x, ...)

## S3 method for class 'gjam'
summary(object, ...)
```

Arguments

formula	R formula for model, e.g., $\sim x_1 + x_2$.
xdata	data.frame containing predictors in formula. If not found in xdata variables, they must be available from the user's workspace.
ydata	n by S response matrix or data.frame. Column names are unique labels, e.g., species names. All columns will be included in the analysis.
modelList	list specifying inputs, including ng (number of Gibbs steps), burnin, and typeNames. Can include the number of holdouts for out-of-sample prediction, holdoutN. See Details .
x	object of class gjam .
object	currently, also an object of class gjam .
...	further arguments not used here.

Details

Note that formula begins with $\sim$, not $y \sim$. The response matrix is passed in the form of a n by S matrix or data.frame ydata.

Both predictors in xdata and responses in ydata can include missing values as NA. Factors in xdata should be declared using factor. For computational stability variables that are not factors are standardized by mean and variance, then transformed back to original scales in output. To retain a variable in its original scale during computation include it in the character string notStandard as part of the list modelList. (example shown in the vignette on traits).

modelList has these defaults and provides these options:

ng = 2000, number of Gibbs steps.

burnin = 500, no. initial steps, must be less than ng.

typeName can be 'PA' (presenceAbsence), 'CON' (continuous on $(-\infty, \infty)$), 'CA' (continuous abundance, zero censoring), 'DA' (discrete abundance), 'FC' (fractional composition), 'CC' (count composition), 'OC' (ordinal counts), 'CAT' (categorical classes). typeName can be a single value that applies to all columns in ydata, or there can be one value for each column.

holdoutN = 0, number of observations to hold out for out-of-sample prediction.

holdoutIndex = numeric(0), numeric vector of observations (row numbers) to holdout for out-of-sample prediction.

censor = NULL, list specifying columns, values, and intervals for censoring, see [gjamCensorY](#).

effort = NULL, list containing 'columns', a vector of length $\leq S$ giving the names of columns in in y, and 'values', a length-n vector of effort or a n by S matrix (see Examples). effort can be plot area, search time, etc. for discrete count data 'DA'.

FULL = F in modelList will save full prediction chains in \$chains\$ygibbs.

notStandard = NULL, character vector of column names in xdata that should not be standardized.

reductList = list(N = 20, r = 3), list of dimension reduction parameters, invoked when reductList is included in modelList or automatically when ydata has too many columns. See vignette on Dimension Reduction.

random, character string giving the name of a column in xdata that will be used to specify random effects. The random group column should be declared as a factor. There should be replication, i.e., each group level occurs multiple times.

REDUCT = F in modelList overrides automatic dimension reduction.

FCgroups, CCgroups, are length-S vectors assigned to columns in ydata indicating composition 'FC' or 'CC' group membership. For example, if there are two 'CA' columns in ydata followed by two groups of fractional composition data, each having three columns, then typeName = c('CA', 'CA', 'FC', 'FC', 'FC', 'FC', 'FC', 'FC') and FCgroups = c(0, 0, 1, 1, 1, 2, 2, 2). note: gjamSimData is not currently set up to simulate multiple composition groups, but gjam will model it.

PREDICTX = T executes inverse prediction of x. Speed-up by setting PREDICTX = F.

ematAlpha = .5 is the probability assigned for conditional and marginal independence in the ematrix.

traitList = list(plotByTrait, traitTypes, specByTrait), list of trait objects. See vignette on Trait analysis.

More detailed vignettes can be obtained with:

```
browseVignettes('gjam')
```

Value

Returns an object of [class](#) "gjam", which is a list containing the following components:

call	function call
chains	list of MCMC matrices, each with ng rows; includes coefficients bgibbs(Q*S columns), bgibbsUn (unstandardized for x), sensitivity fgibbs (Q1 columns), and fbgibbs (Q1 columns, where Q1 = Q - 1, unless there are multilevel factors); covariance sgibbs has $S*(S+1)/2$ columns (REDUCT == F) or $N*r$ columns (REDUCT == T).

<code>fit</code>	list of diagnostics (DIC, rmspeAll, rmspeBySpec, xscore, yscore).
<code>inputs</code>	list of input summaries, including <code>breakMat</code> (partition matrix), <code>classBySpec</code> (interval assignment), <code>designTable</code> (summary of design matrix), <code>[factorBeta, interBeta, intMat, linFactor]</code> (factor and interaction information), <code>other</code> , <code>notOther</code> (response columns to exclude and not), <code>[standMat, standRows, standX]</code> means and variances to standardize x, <code>[x, xdata, y]</code> cleaned versions of data.
<code>missing</code>	list of missing objects, including locations for predictors <code>xmiss</code> and responses <code>ymiss</code> in <code>xdata</code> and <code>ydata</code> , respectively, predictor means <code>xmissMu</code> and standard errors <code>xmissSe</code> , response means <code>ymissMu</code> and standard errors <code>ymissSe</code> .
<code>modellist</code>	list of model specifications from input <code>modellist</code> .
<code>parameters</code>	list of parameter estimates, including coefficient matrices on standardized (<code>betaMu</code> , <code>betaSe</code>), unstandardized (<code>betaMuUn</code> , <code>betaSeUn</code>), and dimensionless (<code>fBetaMu</code> , <code>fBetaSd</code>) scales; correlation (<code>corMu</code> , <code>corSe</code>) and covariance (<code>sigMu</code> , <code>sigSe</code>) matrices; sensitivities to predictors (<code>fmatrix</code> , <code>fMu</code> , <code>fSe</code>); environmental response matrix (<code>ematrix</code>), with locations of zero elements, conditionally (<code>whConZero</code>) and marginally (<code>whichZero</code>), set at probability level <code>modellist\$ematAlpha</code> ; and latent variables (<code>wMu</code> , <code>wSd</code>).
<code>prediction</code>	list of predicted values, including species richness (responses predicted > 0); inverse predicted x (<code>xpredMu</code> , <code>xpredSd</code>) and predicted y (<code>ypredMu</code> , <code>ypredSd</code>) matrices.

If **traits** are modeled, then parameters will additionally include `betaTraitMu`, `betaTraitSe` (coefficients), `sigmaTraitMu`, `sigmaTraitSe` (covariance). `prediction` will additionally include `tMuOrd` (ordinal trait means), `tMu`, `tSe` (trait predictions).

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs*, 87, 34-56.

See Also

[gjamSimData](#) simulates data

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

website 'http://sites.nicholas.duke.edu/clarklab/code/'.

Examples

```
## Not run:
## combinations of scales
types <- c('DA', 'DA', 'OC', 'OC', 'OC', 'OC', 'CON', 'CON', 'CON', 'CON', 'CON', 'CA', 'CA', 'PA', 'PA')
```

```

f    <- gjamSimData(S = length(types), typeNames = types)
m1   <- list(ng = 500, burnin = 50, typeNames = f$typeNames)
out  <- gjam(f$formula, f$xdata, f$ydata, modelList = m1)
summary(out)

# repeat with ng = 5000, burnin = 500, then plot data:
p1   <- list(trueValues = f$trueValues)
gjamPlot(out, plotPars = p1)

## discrete abundance with heterogeneous effort
S    <- 5
n    <- 1000
eff  <- list( columns = 1:S, values = round(runif(n,.5,5),1) )
f    <- gjamSimData(n, S, typeNames='DA', effort=eff)
m1   <- list(ng = 2000, burnin = 500, typeNames = f$typeNames, effort = eff)
out  <- gjam(f$formula, f$xdata, f$ydata, modelList = m1)
summary(out)

# repeat with ng = 2000, burnin = 500, then plot data:
p1   <- list(trueValues = f$trueValues)
gjamPlot(out, plotPars = p1)

## End(Not run)

```

gjamCensorY

*Censor gjam response data***Description**

Returns a list with censored values, intervals, and censored response matrix *y*.

Usage

```
gjamCensorY(values, intervals, y, type='CA', whichcol = c(1:ncol(y)))
```

Arguments

<code>values</code>	Values in <i>y</i> that are censored, specified by intervals
<code>intervals</code>	matrix having two rows and one column for each value in <code>values</code> . The first row holds lower bounds. The second row holds upper bounds. See Examples .
<code>y</code>	Response matrix, <i>n</i> rows by <i>S</i> columns. All values within intervals will be replaced with <code>values</code>
<code>type</code>	Response type, see <code>typeNames</code> in gjam
<code>whichcol</code>	Columns in <i>y</i> that are censored (often not all responses are censored)

Details

Any values in *y* that fall within censored intervals are replaced with censored values. The example below simulates data collected on an 'octave scale': 0, 1, 2, 4, 8, ..., an approach to accelerate data collection with approximate bins.

Value

Returns a list containing two elements.

y	n by S matrix updated with censored values substituted for those falling within intervals.
censor	list containing \$columns that are censored and \$partition, a matrix with 3 rows used in <code>gjam</code> and <code>gjamPlot</code> , one column per censor interval. Rows are values, followed by lower and upper bounds.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

`gjamSimData` simulates data `gjam` analyzes data

A more detailed vignette is can be obtained with:

`browseVignettes('gjam')`

website '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Examples

```
## Not run:
# data in octaves
v <- up <- c(0, 2^c(0:4), Inf)
dn <- c(-Inf, v[-length(v)])
i <- rbind( dn, up ) # intervals

f <- gjamSimData(n = 2000, S = 15, Q = 3, typeNames='CA')
y <- f$y
cc <- c(3:6) # censored columns
g <- gjamCensorY(values = v, intervals = i, y = y, whichcol = cc)
y[,cc] <- g$y # replace columns
m1 <- list(ng = 500, burnin = 100, censor = g$censor, typeNames = f$typeNames)
output <- gjam(f$formula, xdata = f$xdata, ydata = y, modelList = m1)

#repeat with ng = 2000, burnin = 500, then:
p1 <- list(trueValues = f$trueValues, width = 3, height = 3)
gjamPlot(output, p1)

# upper detection limit
up <- 5
v <- up
i <- matrix(c(up,Inf),2)
```



```

rownames(i) <- c('down','up')

f <- gjamSimData(typeNames='CA')
g <- gjamCensorY(values = v, intervals = i, y = f$y)
ml <- list(ng = 500, burnin = 100, censor = g$censor, typeNames = f$typeNames)
out <- gjam(f$formula, xdata = f$xdata, ydata = g$y, modelList = ml)

#repeat with ng = 2000, burnin = 500, then:
pl <- list(trueValues = f$trueValues, width = 3, height = 3)
gjamPlot(out, pl)

# lower detection limit
lo <- .001
values <- upper <- lo
intervals <- matrix(c(-Inf,lo),2)
rownames(intervals) <- c('lower','upper')

## End(Not run)

```

gjamConditionalParameters

Parameters for gjam conditional prediction

Description

Conditional parameters quantify the direct effects of predictors including those that come through other species.

Usage

```
gjamConditionalParameters(output, conditionOn, nsim = 2000)
```

Arguments

output	object of <code>class</code> "gjam".
conditionOn	a character vector of responses to condition on (see Details).
nsim	number of draws from the posterior distribution.

Details

Responses in ydata are random with a joint distribution that comes through the residual covariance having mean matrix parameters\$`sigMu` and standard error matrix parameters\$`sigSe`. Still, it can be desirable to use some responses, along with covariates, as predictors of others. The responses (columns) in ydata are partitioned into two groups, a group to condition on (the names included in character vector conditionOn) and the remaining columns. conditionOn gives the names of response variables (colnames for ydata). The conditional distribution is parameterized as the sum of effects that come directly from predictors in xdata, in a matrix C, and from the other responses, i.e., those in conditionOn, a matrix A. A third matrix P holds the conditional covariance.

See examples below.

Value

Amu	posterior mean for matrix A.
Ase	standard error for matrix A.
Atab	parameter summary for matrix A.
Cmu	posterior mean for matrix C.
Cse	standard error for matrix C.
Ctab	parameter summary for matrix C.
Pmu	posterior mean for matrix P.
Pse	standard error for matrix P.
Ptab	parameter summary for matrix P.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Qiu, T., S. Shubhi, C. W. Woodall, and J.S. Clark. 2021. Niche shifts from trees to fecundity to recruitment that determine species response to climate change. *Frontiers in Ecology and Evolution* 9, 863. 'https://www.frontiersin.org/article/10.3389/fevo.2021.719141'.

See Also

[gjamSimData](#) simulates data

[gjam](#) fits the model

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

web site 'http://sites.nicholas.duke.edu/clarklab/code/'.

Examples

```
## Not run:
f <- gjamSimData(n = 200, S = 10, Q = 3, typeNames = 'CA')
m1 <- list(ng = 2000, burnin = 50, typeNames = f$typeNames, holdoutN = 10)
output <- gjam(f$formula, f$xdata, f$ydata, modelList = m1)

# condition on three species
gjamConditionalParameters( output, conditionOn = c('S1','S2','S3') )

## End(Not run)
```

gjamDeZero	<i>Compress (de-zero) gjam data</i>
------------	-------------------------------------

Description

Returns a de-zeroed (sparse matrix) version of matrix `ymat` with objects needed to re-zero it.

Usage

```
gjamDeZero(ymat)
```

Arguments

<code>ymat</code>	n by S response matrix
-------------------	------------------------

Details

Many abundance data sets are mostly zeros. [gjamDeZero](#) extracts non-zero elements for storage.

Value

Returns a list containing the de-zeroed `ymat` as a vector `yvec`.

<code>yvec</code>	non-zero elements of <code>ymat</code>
<code>n</code>	no. rows of <code>ymat</code>
<code>S</code>	no. cols of <code>ymat</code>
<code>index</code>	index for non-zeros
<code>ynames</code>	column names of <code>ymat</code>

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2016. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjamReZero](#) to recover `ymat`
`browseVignettes('gjam')`
website '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Examples

```
## Not run:
library(repmis)
source_data("https://github.com/jimclarkatduke/gjam/blob/master/fungEnd.RData?raw=True")

ymat <- gjamReZero(fungEnd$yDeZero) # OTUs stored without zeros
length(fungEnd$yDeZero$yvec)        # size of stored version
length(ymat)                        # full size
yDeZero <- gjamDeZero(ymat)
length(yDeZero$yvec)                # recover de-zeroed vector

## End(Not run)
```

`gjamFillMissingTimes` *Fill out data for time series (state-space) gjam*

Description

Fills in predictor, response, and effort matrices for time series data where there are multiple multivariate time series. Time series gjam is here <https://htmlpreview.github.io/?https://github.com/jimclarkatduke/gjam/blob/master/gjamTimeMsVignette.html>

Usage

```
gjamFillMissingTimes(xdata, ydata, edata, groupCol, timeCol, groupVars = groupCol,
                     FILLMEANS = FALSE, typeNames = NULL, missingEffort = .1)
```

Arguments

<code>xdata</code>	<code>n</code> by <code>Q</code> data.frame holding predictor variables
<code>ydata</code>	<code>n</code> by <code>S</code> matrix holding response variables
<code>edata</code>	<code>n</code> by <code>S</code> matrix holding effort
<code>groupCol</code>	column name in <code>xdata</code> for group variable, i.e., observations part of the same time series
<code>timeCol</code>	column name in <code>xdata</code> for time index
<code>groupVars</code>	character vector of column names in <code>xdata</code> having values that are fixed for a value of <code>groupCol</code> , i.e., they do not change with time index in <code>timeCol</code>
<code>FILLMEANS</code>	fill new rows in <code>ydata</code> with mean for <code>groupCol</code> times <code>missingEffort</code> ; otherwise NA
<code>typeNames</code>	typenames current limited to 'DA' for discrete counts
<code>missingEffort</code>	effort assigned to missing values of <code>edata</code> and <code>ydata</code>

Details

Missing times in the data occur where there are gaps in `timeCol` column of `xdata` and the initial time 0 for each sequence. New versions of the data have NA (`xdata`) or prior values with appropriate weight (`ydata`). Missing times are filled in `xdata`, `ydata`, `edata`, including a time 0 which serves as a prior mean for `ydata` for time 1. The group and time indices in columns `groupCol` and `timeCol` of `xdata` reference the time for a given time series. Missing values in the columns `groupVars` of `xdata` are filled automatically. This assumes that values for these variables are fixed for the group. If `FILLMEANS`, the missing values in `ydata` are filled with means for the group and given a low weight specified in `missingEffort`.

Value

A list containing the following:

<code>xdata</code>	filled version of <code>xdata</code>
<code>ydata</code>	filled version of <code>ydata</code>
<code>edata</code>	filled version of <code>edata</code>
<code>timeList</code>	time indices used for computation, including, <code>timeZero</code> (row numbers in new data where each time series begins, with times = 0), <code>timeLast</code> (row numbers in new data where each time series ends), <code>rowInserts</code> (row numbers for all inserted rows), <code>noEffort</code> (rows for which effort in <code>edata</code> is filled with <code>missingEffort</code>)

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J. S., C. L. Scher, and M. Swift. 2020. The emergent interactions that govern biodiversity change. *Proceedings of the National Academy of Sciences*, 117, 17074-17083.

See Also

[gjam](#) for more on `xdata`, `ydata`, and `effort`.

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

web site '<http://sites.nicholas.duke.edu/clarklab/code/>'.

gjamIIE

*Indirect effects and interactions for gjam data***Description**

Evaluates direct, indirect, and interactions from a [gjam](#) object. Returns a list of objects that can be plotted by [gjamIIEplot](#).

Usage

```
gjamIIE(output, xvector, MEAN = T, keepNames = NULL, omitY = NULL,
        sdScaleX = T, sdScaleY = F)
```

Arguments

output	object of class inheriting from "gjam".
xvector	vector of predictor values, with names, corresponding to columns in output\$x.
MEAN	logical, if false, then median used.
omitY	character vector of columns in output\$y to omit from calculations.
keepNames	character vector of columns in output\$y. If omitted, all columns used.
sdScaleX	standardize coefficients to X scale.
sdScaleY	standardize coefficients to correlation scale.

Details

For plotting or recovering effects. The list `fit$IIE` has matrices for main effects (`mainEffect`), interactions (`intEffect`), direct effects (`dirEffect`), indirect effects (`indEffectTo`), and standard deviations for each. The direct effects are the sum of main effects and interactions. The indirect effects include main effects and interactions that come through other species, determined by covariance matrix `sigma`.

If `sdScaleX = T` effects are standardandardized from the Y/X to Y scale. This is the typical standardization for predictor variables. If `sdScaleY = T` effects are given on the correlation scale. If both are true effects are dimensionless. See the [gjam vignette](#) on dimension reduction.

Value

A list of objects for plotting by [gjamIIEplot](#).

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2016. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjamIIEplot](#) plots output from [gjamIIE](#)

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

web site '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Examples

```
## Not run:
sim <- gjamSimData(S = 12, Q = 5, typeNames = 'CA')
m1 <- list(ng = 50, burnin = 5, typeNames = sim$typeNames)
out <- gjam(sim$formula, sim$xdata, sim$ydata, modelList = m1)

xvector <- colMeans(out$inputs$xStand) #predict at mean values for data
xvector[1] <- 1

fit <- gjamIIE(output = out, xvector)

gjamIIEplot(fit, response = 'S1', effectMu = c('main','ind'),
            effectSd = c('main','ind'), legLoc = 'topleft')

## End(Not run)
```

gjamIIEplot

Plots indirect effects and interactions for gjam data

Description

Using the object returned by [gjamIIEplot](#) generates a plot for a response variable.

Usage

```
gjamIIEplot(fit, response, effectMu, effectSd = NULL,
            ylim = NULL, col='black', legLoc = 'topleft', cex = 1)
```

Arguments

fit	object from gjamIIE .
response	name of a column in fit\$y to plot.
effectMu	character vector of mean effects to plot, can include 'main', 'int', 'direct', 'ind'.

effectSd	character vector can include all or some of effectMu.
ylim	vector of two values defines vertical axis range.
col	vector of colors for barplot.
legLoc	character for legend location.
cex	font size.

Details

For plotting direct effects, interactions, and indirect effects from an object `fit` generated by `gjamIIE`. The character vector supplied as `effectMu` can include main effects ('main'), interactions ('int'), main effects plus interactions ('direct'), and/or indirect effects ('ind'). The list `effectSd` draws 0.95 predictive intervals for all or some of the effects listed in `effectMu`. Bars are contributions of each effect to the response.

For factors, effects are plotted relative to the mean over all factor levels.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjamIIE](#) generates output for `gjamIIEplot`

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

web site '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Examples

```
## Not run:
f <- gjamSimData(S = 10, Q = 6, typeNames = 'OC')
m1 <- list(ng = 50, burnin = 5, typeNames = f$typeNames)
out <- gjam(f$formula, f$xdata, f$ydata, modelList = m1)

xvector <- colMeans(out$inputs$xStand) #predict at mean values for data, standardized x
xvector[1] <- 1

fit <- gjamIIE(out, xvector)

gjamIIEplot(fit, response = 'S1', effectMu = c('main','ind'),
            effectSd = c('main','ind'), legLoc = 'topleft')

## End(Not run)
```

gjamOrdination	<i>Ordinate gjam data</i>
----------------	---------------------------

Description

Ordinate data from a gjam object using correlation corresponding to reponse matrix E.

Usage

```
gjamOrdination(output, specLabs = NULL, col = NULL, cex = 1,
               PLOT=T, method = 'PCA')
```

Arguments

output	object of <code>class</code> "gjam".
specLabs	character vector of variable names in <code>colnames(output\$y)</code> .
col	character vector of columns in <code>output\$y</code> to label in plots.
cex	text size in plot.
PLOT	logical, if true, draw plots.
method	character variable can specify 'NMDS'.

Details

Ordinates the response correlation ematrix contained in `output$parameterTables`. If `method = 'PCA'` returns eigenvalues and eigenvectors. If `method = 'PCA'` returns three NMDS dimensions. If `PLOT`, then plots will be generated. Uses principle components analysis or non-metric multidimensional scale (NMDS).

Value

eVecs	S x S or, if there is an other response variable to be excluded, S-1 x S-1 matrix of eigenvectors for species (rows) by eigenvectors (columns).
eValues	If <code>method = 'PCA'</code> returns length-S or, there is an other response variable to be excluded, length-S-1 vector of eigenvalues. If <code>method = 'NMDS'</code> this variable is <code>NULL</code> .

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjam](#) fits the data

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

website 'http://sites.nicholas.duke.edu/clarklab/code/'.

Examples

```
## Not run:
f      <- gjamSimData(S = 30, typeNames = 'CA')
ml     <- list(ng = 1000, burnin = 200, typeNames = f$typeNames, holdoutN = 10)
output <- gjam(f$formula, f$xdata, f$ydata, modelList = ml)
ePCA   <- gjamOrdination(output, PLOT=TRUE)
eNMDS  <- gjamOrdination(output, PLOT=TRUE, method='NMDS')

## End(Not run)
```

gjamPlot

Plot gjam analysis

Description

Constructs plots of posterior distributions, predictive distributions, and additional analysis from output of [gjam](#).

Usage

```
gjamPlot(output, plotPars)
```

Arguments

output	object of class "gjam"
plotPars	list having default values described in Details

Details

plotPars a list that can contain the following, listed with default values:

PLOTY = T	plot predicted y.
PLOTX = T	plot inverse predicted x.
PREDICTX = T	inverse prediction of x; does not work if PREDICTX = F in link{gjam}.
ncluster	number of clusters to highlight in cluster diagrams, default based on S.
CORLINES = T	draw grid lines on grid plots of R and E.
cex = 1	text size for grid plots, see par .
BETAGRID = T	draw grid of beta coefficients.
PLOTALLY = F	an individual plot for each column in y.

SMALLPLOTS = T	avoids plot margin error on some devices, better appearance if FALSE.
GRIDPLOTS = F	cluster and grid plots derived from parameters; matrices R and E are discussed in Clark et al. (2017).
SAVEPLOTS = F	plots saved in pdf format.
outfolder = 'gjamOutput'	folder for plot files if SAVEPLOTS = T.
width, height = 4	can be small values, in inches, to avoid plot margin error on some devices.
specColor = 'black'	color for posterior box-and-whisker plots.
ematAlpha = .95	prob threshold used to infer that a covariance value in Emat is not zero.
ncluster = 4	number of clusters to identify in ematrix.

The 'plot margin' errors mentioned above are device-dependent. They can be avoided by specifying small width, height (in inches) and by omitting the grid plots (GRIDPLOTS = F). If plotting does not produce a 'plot margin error', better appearance is obtained with SMALLPLOTS = F.

Names will not be legible for large numbers of species. Specify specLabs = F and use a character vector for specColor to identify species groups (see the gjam vignette on dimension reduction).

Box and whisker plots bound 0.68 and 0.95 credible and predictive intervals.

Value

Summary tables of parameter estimates are:

betaEstimates	Posterior summary of beta coefficients.
clusterIndex	cluster index for responses in grid/cluster plots.
clusterOrder	order for responses in grid/cluster plots.
eComs	groups based on clustering ematrix.
ematrix	S X S response correlation matrix for E.
eValues	eigenvalues of ematrix.
eVecs	eigenvectors of ematrix.
fit	list containing DIC, score, and rmspe.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjam](#) A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

website 'http://sites.nicholas.duke.edu/clarklab/code/'.

Examples

```
## Not run:
## ordinal data
f <- gjamSimData(S = 15, Q = 3, typeNames = 'OC')
ml <- list(ng = 1500, burnin = 500, typeNames = f$typeNames, holdoutN = 10)
out <- gjam(f$formula, f$xdata, f$ydata, modelList = ml)

# repeat with ng = 2000, burnin = 500, then plot data here:
pl <- list(trueValues = f$trueValues, width=3, height=2)
fit <- gjamPlot(output = out, plotPars = pl)

## End(Not run)
```

gjamPoints2Grid

Incidence point pattern to grid counts

Description

From point pattern data in (x, y) generates counts on a lattice supplied by the user or specified by lattice size or density. For analysis in [gjam](#) as counts (known effort) or count composition (unknown effort) data.

Usage

```
gjamPoints2Grid(specs, xy, nxy = NULL, dxy = NULL,
  predGrid = NULL, effortOnly = TRUE)
```

Arguments

specs	character vector of species names or codes.
xy	matrix with rows = length(specs) and columns for (x, y).
nxy	length-2 numeric vector with numbers of points evenly spaced on (x, y).
dxy	length-2 numeric vector with distances for points evenly spaced on (x, y).
predGrid	matrix with 2 columns for (x, y).
effortOnly	logical to return only points where counts are positive (e.g., effort is unknown).

Details

For incidence data with species names specs and locations (x, y) constructs a lattice based a prediction grid predGrid, at a density of (dx, dy), or with numbers of lattice points (nx, ny). If effortOnly = T, returns only points with non-zero values.

A prediction grid predGrid would be passed when counts by locations of known effort are required or where multiple groups should be assign to the same lattice points.

The returned gridBySpec can be analyzed in [gjam](#) with known effort as count data "DA" or with unknown effort as count composition data "CC".

Value

gridBySpec	matrix with rows for grid locations, columns for counts by species.
predGrid	matrix with columns for (x, y) and rows matching gridBySpec.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2016. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjam](#) A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

Examples

```
## Not run:
## random data
n <- 100
s <- sample( letters[1:3], n, replace = TRUE)
xy <- cbind( rnorm(n,0,.2), rnorm(n,10,2) )

nx <- ny <- 5                                # uniform 5 X 5 lattice
f <- gjamPoints2Grid(s, xy, nxy = c(nx, ny))
plot(f$predGrid[,1], f$predGrid[,2], cex=.1, xlim=c(-1,1), ylim=c(0,20),
     xlab = 'x', ylab = 'y')
text(f$predGrid[,1], f$predGrid[,2], rowSums(f$gridBySpec))

dx <- .2                                     # uniform density
dy <- 1.5
g <- gjamPoints2Grid(s, xy, dxy = c(dx, dy))
text(g$predGrid[,1], g$predGrid[,2], rowSums(g$gridBySpec), col='brown')

p <- cbind( runif(30, -1, 1), runif(30, 0, 20) ) # irregular lattice
h <- gjamPoints2Grid(s, xy, predGrid = p)
text(h$predGrid[,1], h$predGrid[,2], rowSums(h$gridBySpec), col='blue')

## End(Not run)
```

gjamPredict	<i>Predict gjam data</i>
-------------	--------------------------

Description

Predicts data from a gjam object, including conditional and out-of-sample prediction.

Usage

```
gjamPredict(output, newdata = NULL, y2plot = NULL, ylim = NULL,
            FULL = FALSE)
```

Arguments

output	object of <code>class</code> "gjam".
newdata	a list of data for prediction, see Details .
y2plot	character vector of columns in output\$y to plot.
ylim	vector of lower and upper bounds for prediction plot
FULL	will return full chains for predictions as output\$ychains

Details

If newdata is not specified, the response is predicted from xdata as an in-sample prediction. If newdata is specified, prediction is either conditional or out-of-sample.

Conditional prediction on a new set of y values is done if newdata includes the matrix ycondData, which holds columns to condition on. ycondData must be a matrix and have column names matching those in y that it will replace. ycondData must have at least one column, but fewer than ncol(y) columns. Columns not included in ycondData will be predicted conditionally. Note that conditional prediction can be erratic if the observations on which the prediction is conditioned are unlikely given the model.

Alternatively, the list newdata can include a new version of xdata for out-of-sample prediction. The version of xdata passed in newdata has the columns with the same names and variable types as xdata passed to `gjam`. Note that factor levels must also match those included when fitting the model. All columns in y will be predicted out-of-sample.

For count composition data the effort (total count) is 1000.

Because there is no out-of-sample effort for 'CC' data, values are predicted on the [0, 1] scale.

See examples below.

Value

x	design matrix.
sdList	list of predictive means and standard errors includes yMu, yPe (predictive mean, SE), wMu, wSe (mean latent states and SEs)

piList	predictive intervals, only generated if <code>length(y) < 10000</code> , includes yLo, yHi (0.025, 0.975) prediction interval, wLo, wHi (0.025, 0.975) for latent states
prPresent	n x S matrix of probabilities of presence
ematrix	effort
ychains	full prediction chains if FULL = T

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2016. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs*, 87, 34-56.

See Also

[gjamSimData](#) simulates data

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

web site '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Examples

```
## Not run:
S <- 10
f <- gjamSimData(n = 200, S = S, Q = 3, typeNames = 'CC')
m1 <- list(ng = 1500, burnin = 50, typeNames = f$typeNames, holdoutN = 10)
out <- gjam(f$formula, f$xdata, f$ydata, modelList = m1)

# predict data
cols <- c('#018571', '#a6611a')
par(mfrow=c(1,3),bty='n')
gjamPredict(out, y2plot = colnames(f$ydata)) # predict the data in-sample
title('full sample')

# out-of-sample prediction
xdata <- f$xdata[1:20,]
xdata[,3] <- mean(f$xdata[,3]) # mean for x[,3]
xdata[,2] <- seq(-2,2,length=20) # gradient x[,2]
newdata <- list(xdata = xdata, nsim = 50)
p1 <- gjamPredict( output = out, newdata = newdata)

# plus/minus 1 prediction SE, default effort = 1000
x2 <- p1$x[,2]
ylim <- c(0, max(p1$sedList$yMu[,1] + p1$sedList$yPe[,1]))
plot(x2, p1$sedList$yMu[,1],type='l',lwd=2, ylim=ylim, xlab='x2',
     ylab = 'Predicted', col = cols[1])
lines(x2, p1$sedList$yMu[,1] + p1$sedList$yPe[,1], lty=2, col = cols[1])
```

```

lines(x2, p1$sedList$yMu[,1] - p1$sedList$yPe[,1], lty=2, col = cols[1])

# upper 0.95 prediction error
lines(x2, p1$piList$yLo[,1], lty=3, col = cols[1])
lines(x2, p1$piList$yHi[,1], lty=3, col = cols[1])
title('SE and prediction, Sp 1')

# conditional prediction, assume first species is absent
ydataCond <- out$inputs$y[,1,drop=FALSE]*0 # set first column to zero
newdata <- list(ydataCond = ydataCond, nsim=50)
p0 <- gjamPredict(output = out, newdata = newdata)

ydataCond <- ydataCond + 10 # first column is 10
newdata <- list(ydataCond = ydataCond, nsim=50)
p1 <- gjamPredict(output = out, newdata = newdata)

s <- 4 # species chosen at random to compare
ylim <- range( p0$sedList$yMu[,s], p1$sedList$yMu[,s] )
plot(out$inputs$y[,s],p0$sedList$yMu[,s], cex=.2, col=cols[1],
     xlab = 'Observed', ylab = 'Predicted', ylim = ylim)
abline(0,1,lty=2)
points(out$inputs$y[,s],p1$sedList$yMu[,s], cex=.2, col=cols[2])
title('Cond. on 1st Sp')
legend( 'topleft', c('first species absent', 'first species = 10'),
       text.col = cols, bty = 'n')

# conditional, out-of-sample
n <- 1000
S <- 10
f <- gjamSimData(n = n, S = S, Q = 3, typeNames = 'CA')

holdOuts <- sort( sample(n, 50) )

xdata <- f$xdata[-holdOuts,] # fitted data
ydata <- f$ydata[-holdOuts,]

xx <- f$xdata[holdOuts,] # use for prediction
yy <- f$ydata[holdOuts,]

m1 <- list(ng = 2000, burnin = 500, typeNames = f$typeNames) # fit the non-holdouts
out <- gjam(f$formula, xdata, ydata, modelList = m1)

cdex <- sample(S, 4) # condition on 4 species
ndex <- c(1:S)[-cdex] # conditionally predict others

newdata <- list(xdata = xx, ydataCond = yy[,cdex], nsim = 200) # conditionally predict out-of-sample
p2 <- gjamPredict(output = out, newdata = newdata)

par(bty='n', mfrow=c(1,1))
plot( as.matrix(yy[,ndex]), p2$sedList$yMu[,ndex],
     xlab = 'Observed', ylab = 'Predicted', cex=.3, col = cols[1])
abline(0,1,lty=2)
title('RMSPE')

```



```

mspeC <- sqrt( mean( (as.matrix(yy[,ndex]) - p2$sdList$yMu[,ndex])^2 ) )

#predict unconditionally, out-of-sample
newdata <- list(xdata = xx, nsim = 200 )
p1 <- gjamPredict(out, newdata = newdata)

points( as.matrix(yy[,ndex]), p1$sdList$yMu[,ndex], col=cols[2], cex = .3)
mspeU <- sqrt( mean( (as.matrix(yy[,ndex]) - p1$sdList$yMu[,ndex])^2 ) )

e1 <- paste( 'cond, out-of-sample =', round(mspeC, 2) )
e2 <- paste( 'uncond, out-of-sample =', round(mspeU, 2) )

legend('topleft', c(e1, e2), text.col = cols, bty = 'n')

## End(Not run)

```

gjamPriorTemplate	<i>Prior coefficients for gjam analysis</i>
-------------------	---

Description

Constructs coefficient matrices for low and high limits on the uniform prior distribution for beta.

Usage

```
gjamPriorTemplate(formula, xdata, ydata, lo = NULL, hi = NULL)
```

Arguments

formula	object of class formula, starting with ~, matches the formula passed to gjam
xdata	n x Q observation by predictor data.frame
ydata	n x Q observation by response data.frame
lo	list of lower limits
hi	list of upper limits

Details

The prior distribution for a coefficient $\beta_{[q,s]}$ for predictor q and response s , is $\text{dunif}(\text{lo}[q,s], \text{hi}[q,s])$. `gjamPriorTemplate` generates these matrices. The default values are $(-\text{Inf}, \text{Inf})$, i.e., all values in `lo` equal to $-\text{Inf}$ and `hi` equal to Inf . These templates can be modified by changing specific values in `lo` and/or `hi`.

Alternatively, desired lower limits can be passed as the list `lo`, assigned to names in `xdata` (same limit for all species in `ydata`), in `ydata` (same limit for all predictors in `xdata`), or both, separating names in `xdata` and `ydata` by `"_"`. The same convention is used for upper limits in `hi`.

These matrices are supplied in as list `betaPrior`, which is included in `modelList` passed to `gjam`. See examples and `browseVignettes('gjam')`.

Note that the informative prior slows computation.

Value

A list containing two matrices. `lo` is a $Q \times S$ matrix of lower coefficient limits. `hi` is a $Q \times S$ matrix of upper coefficient limits. Unless specified in `lo`, all values in `lo` = -Inf. Likewise, unless specified in `hi`, all values in `hiBeta` = -Inf.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjam](#)

Examples

```
## Not run:
library(repmis)
source_data("https://github.com/jimclarkatduke/gjam/blob/master/forestTraits.RData?raw=True")

xdata      <- forestTraits$xdata
plotByTree <- gjamReZero(forestTraits$treesDeZero) # re-zero
traitTypes <- forestTraits$traitTypes
specByTrait <- forestTraits$specByTrait

tmp <- gjamSpec2Trait(pbys = plotByTree, sbys = specByTrait,
                     tTypes = traitTypes)
tTypes <- tmp$traitTypes
traity <- tmp$plotByCWM
censor <- tmp$censor

formula <- as.formula(~ temp + deficit)
lo <- list(temp_gmPerSeed = 0, temp_dioecious = 0 ) # positive effect on seed size, dioecy
b  <- gjamPriorTemplate(formula, xdata, ydata = traity, lo = lo)

m1 <- list(ng=3000, burnin=1000, typeNames = tTypes, censor = censor, betaPrior = b)
out <- gjam(formula, xdata, ydata = traity, modelList = m1)

S  <- ncol(traity)
sc <- rep('black',S)
sc[colnames(traity)]
pl <- list(specColor = sc)
gjamPlot(output = out, plotPars = pl)

## End(Not run)
```

gjamReZero	<i>Expand (re-zero) gjam data</i>
------------	-----------------------------------

Description

Returns a re-zeroed matrix *y* from the de-zeroed vector, a sparse matrix.

Usage

```
gjamReZero( yDeZero )
```

Arguments

yDeZero	list created by gjamReZero containing number of rows <i>n</i> , number of columns <i>S</i> , index for non-zeros <i>index</i> , the vector of non-zero values <i>yvec</i> , and the column names <i>yname</i> s.
---------	--

Details

Many abundance data sets are mostly zeros. `gjamReZero` recovers the full matrix from de-zeroed list `yDeZero` written by [gjamDeZero](#)

Value

<i>ymat</i>	re-zeroed <i>n</i> by <i>S</i> matrix.
-------------	--

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2016. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjamDeZero](#) to de-zero *ymat*
`browseVignettes('gjam')`
website: `'http://sites.nicholas.duke.edu/clarklab/code/'`.

Examples

```
## Not run:
library(repmis)
source_data("https://github.com/jimclarkatduke/gjam/blob/master/fungEnd.RData?raw=True")
ymat <- gjamReZero(fungEnd$yDeZero) # OTUs stored without zeros
length(fungEnd$yDeZero$yvec)       # size of stored version
length(ymat)                        # full size

## End(Not run)
```

gjamSensitivity	<i>Sensitivity coefficients for gjam</i>
-----------------	--

Description

Evaluates sensitivity coefficients for full response matrix or subsets of it. Uses output from [gjam](#). Returns a matrix of samples by predictors.

Usage

```
gjamSensitivity(output, group = NULL, nsim = 100, PERSPECIES = TRUE)
```

Arguments

output	object fitted with gjam.
group	character vector of response-variable names from output\$inputs\$y.
nsim	number of samples from posterior distribution.
PERSPECIES	divide variance by number of species in the group

Details

Sensitivity to predictors of entire response matrix or a subset of it, identified by the character string group. The equations for sensitivity are given here:

```
browseVignettes('gjam')
```

Value

Returns a nsim by predictor matrix of sensitivities to predictor variables, evaluated by draws from the posterior. Because sensitivities may be compared across groups represented by different numbers of species, PERSPECIES = TRUE returns sensitivity on a per-species basis.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs*, 87, 34-56.

See Also

[gjamSimData](#) simulates data

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

website '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Examples

```
## Not run:
## combinations of scales
types <- c('DA','DA','OC','OC','OC','OC','CC','CC','CC','CC','CC','CA','CA','PA','PA')
f <- gjamSimData(S = length(types), typeNames = types)
ml <- list(ng = 50, burnin = 5, typeNames = f$typeNames)
out <- gjam(f$formula, f$xdata, f$ydata, modelList = ml)

ynames <- colnames(f$y)
group <- ynames[types == 'OC']

full <- gjamSensitivity(out)
cc <- gjamSensitivity(out, group)

nt <- ncol(full)

ylim <- range(rbind(full, cc))

boxplot( full, boxwex = 0.25, at = 1:nt - .21, col='blue', log='y',
         ylim = ylim, xaxt = 'n', xlab = 'Predictors', ylab='Sensitivity')
boxplot( cc, boxwex = 0.25, at = 1:nt + .2, col='forestgreen', add=T,
         xaxt = 'n')
axis(1,at=1:nt,labels=colnames(full))
legend('bottomleft',c('full response','CC data'),
      text.col=c('blue','forestgreen'))

## End(Not run)
```

gjamSimData

Simulated data for gjam analysis

Description

Simulates data for analysis by [gjam](#).

Usage

```
gjamSimData(n = 1000, S = 10, Q = 5, x = NULL, nmiss = 0, typeNames, effort = NULL)
```

Arguments

n	Sample size
S	Number of response variables (columns) in y, typically less than n
Q	Number of predictors (columns) in design matrix $x \ll n$
x	design matrix, if supplied n and Q will be set to <code>nrow(x)</code> and <code>ncol(x)</code> , respectively
nmiss	Number of missing values to in $x \ll n$
typeNames	Character vector of data types, see Details
effort	List containing 'columns' specifying columns to which effort applies, and 'values', a length-n vector of effort per observation.

Details

Generates simulated data and parameters for analysis by [gjam](#). Because both parameters and data are stochastic, not all simulations will give good results.

typeNames can be 'PA' (presenceAbsence), 'CA' (continuous), 'DA' (discrete), 'FC' (fractional composition), 'CC' (count composition), 'OC' (ordinal counts), and 'CAT' (categorical levels). If more than one 'CAT' is included, each defines a multilevel categorical response. One additional type, 'CON' (continuous), is not censored at zero by default.

If defined as a single character value typeNames applies to all columns in y. If not, typeNames is length-S character vector, identifying each response by column in y. If a column 'CAT' is included, a random number of levels will be generated, a, b, c,

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

website '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Value

formula	R formula for model, e.g., $\sim x_1 + x_2$
xdata	data.frame includes columns for predictors in the design matrix
ydata	data.frame for the simulated response
y	response as a n by S matrix as assembled in gjam .
w	n by S latent states
typeY	vector of data types corresponding to columns in y, see Details
typeNames	vector of data types corresponding to columns in ydata
trueValues	list containing true parameter values beta (regression coefficients), sigma (covariance matrix), corSpec (correlation matrix corresponding to sigma), and cuts (partition matrix for ordinal data).
effort	see Arguments .

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2016. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjam](#)

Examples

```
## Not run:
## ordinal data, show true parameter values
sim <- gjamSimData(S = 5, typeNames = 'OC')
sim$ydata[1:5,]                # example data
sim$trueValues$cuts            # simulated partition
sim$trueValues$beta            # coefficient matrix

## continuous data censored at zero, note latent w for obs y = 0
sim <- gjamSimData(n = 5, S = 5, typeNames = 'CA')
sim$w
sim$y

## continuous and discrete data
types <- c(rep('DA',5), rep('CA',4))
sim <- gjamSimData(n = 10, S = length(types), Q = 4, typeNames = types)
sim$typeNames
sim$ydata

## composition count data
sim <- gjamSimData(n = 10, S = 8, typeNames = 'CC')
totalCount <- rowSums(sim$ydata)
cbind(sim$ydata, totalCount) # data with sample effort

## multiple categorical responses - compare matrix y and data.frqme ydata
types <- rep('CAT',2)
sim <- gjamSimData(S = length(types), typeNames = types)
head(sim$ydata)
head(sim$y)

## discrete abundance, heterogeneous effort
S <- 5
n <- 1000
ef <- list( columns = 1:S, values = round(runif(n,.5,5),1) )
sim <- gjamSimData(n, S, typeNames = 'DA', effort = ef)
sim$effort$values[1:20]

## combinations of scales, partition only for 'OC' columns
```

```

types <- c('OC','OC','OC','CC','CC','CC','CC','CC','CA','CA','PA','PA')
sim  <- gjamSimData(S = length(types), typeNames = types)
sim$typeNames
head(sim$ydata)
sim$trueValues$cuts

## End(Not run)

```

gjamSpec2Trait

Ecological traits for gjam analysis

Description

Constructs community-weighted mean-mode (CWMM) trait matrix for analysis with [gjam](#) for n observations, S species, P traits, and M total trait levels.

Usage

```
gjamSpec2Trait(pbys, sbyt, tTypes)
```

Arguments

pbys	$n \times S$ plot by species matrix (presence-absence, abundance)
sbyt	$S \times P$ species by trait matrix
tTypes	P data types for trait columns

Details

Generates the objects needed for a trait response model (TRM). As inputs the sbyt data.frame has P columns containing numeric values, ordinal scores, and categorical variables, identified by data type in tTypes. Additional trait columns can appear in the $n \times M$ output matrix plotByCWMM, because each level of a category becomes a new 'FC' column as a CWMM. Thus, M can exceed P , depending on the number of factors in sbyt. The exception is for categorical traits with only two levels, which can be treated as (0, 1) censored 'CA' data.

As output, the CWMM data types are given in traitTypes.

The list censor = NULL unless some data types are censored. In the example below there are two censored columns.

A detailed vignette on trait analysis is obtained with:

```
browseVignettes('gjam')
```

Value

plotByCWM	$n \times M$ matrix of community-weight means (numeric) or modes (ordinal)
traitTypes	character vector of data types for traits
specByTrait	$S \times M$ matrix translates species to traits
censor	list of censored columns, values, and intervals; see gjamCensorY

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S. 2016. Why species tell us more about traits than traits tell us about species: Predictive models. *Ecology* 97, 1979-1993.

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjam](#), [gjamCensorY](#)

Examples

```
## Not run:
library(repmis)
source_data("https://github.com/jimclarkatduke/gjam/blob/master/forestTraits.RData?raw=True")

xdata      <- forestTraits$xdata
plotByTree <- gjamReZero(forestTraits$treesDeZero) # re-zero
traitTypes <- forestTraits$traitTypes
specByTrait <- forestTraits$specByTrait

tmp <- gjamSpec2Trait(pbys = plotByTree, sbys = specByTrait,
                     tTypes = traitTypes)
tTypes <- tmp$traitTypes
traity <- tmp$plotByCWM
censor <- tmp$censor

m1 <- list(ng=2000, burnin=500, typeNames = tTypes, censor = censor)
out <- gjam(~ temp + stdage + deficit, xdata, ydata = traity, modellist = m1)
gjamPlot( output = out )

## End(Not run)
```

gjamTrimY

Trim gjam response data

Description

Returns a list that includes a subset of columns in y. Rare species can be aggregated into a single class.

Usage

```
gjamTrimY(y, minObs = 2, maxCols = NULL, OTHER = TRUE)
```

Arguments

y	n by S numeric response matrix
minObs	minimum number of non-zero observations
maxCols	maximum number of response variables
OTHER	logical or character string. If OTHER = TRUE, rare species are aggregated in a new column 'other'. A character vector contains the names of columns in y to be aggregated with rare species in the new column 'other'.

Details

Data sets commonly have many responses that are mostly zeros, large numbers of rare species, even singletons. Response matrix y can be trimmed to include only taxa having > minObs non-zero observations or to <= maxCol total columns. The option OTHER is recommended for composition data ('CC', 'FC'), where the 'other' column is taken as the reference class. If there are unidentified species they might be included in this class. [See [gjamSimData](#) for typeName codes].

Value

Returns a list containing three elements.

y	trimmed version of y.
colIndex	length-S vector of indices for new columns in y.
nobs	number of non-zero observations by column in y.

Author(s)

James S Clark, <jimclark@duke.edu>

References

Clark, J.S., D. Nemergut, B. Seyednasrollah, P. Turner, and S. Zhang. 2017. Generalized joint attribute modeling for biodiversity analysis: Median-zero, multivariate, multifarious data. *Ecological Monographs* 87, 34-56.

See Also

[gjamSimData](#) simulates data [gjam](#) analyzes data

A more detailed vignette is can be obtained with:

```
browseVignettes('gjam')
```

web site '<http://sites.nicholas.duke.edu/clarklab/code/>'.

Examples

```
## Not run:
library(repmis)
source_data("https://github.com/jimclarkatduke/gjam/blob/master/forestTraits.RData?raw=True")

y  <- gjamReZero(fungEnd$yDeZero)    # re-zero data
dim(y)
y  <- gjamTrimY(y, minObs = 200)$y   # species in >= 200 observations
dim(y)
tail(colnames(y))    # last column is 'other'

## End(Not run)
```

Index

*** package**

gjam-package, 2

class, 5, 9, 14, 17, 18, 22

GJAM (gjam-package), 2

gjam, 2–4, 4, 7, 8, 10, 13, 14, 18–22, 26, 28–34

gjam-package, 2

gjamCensorY, 3, 5, 7, 32, 33

gjamConditionalParameters, 3, 9

gjamDeZero, 3, 11, 11, 27

gjamFillMissingTimes, 12

gjamIIE, 3, 14, 16

gjamIIEplot, 3, 14, 15, 15

gjamOrdination, 3, 17

gjamPlot, 3, 4, 8, 18

gjamPoints2Grid, 3, 20

gjamPredict, 3, 22

gjamPriorTemplate, 3, 25

gjamReZero, 3, 11, 27, 27

gjamSensitivity, 3, 28

gjamSimData, 3, 4, 6, 8, 10, 23, 29, 29, 34

gjamSpec2Trait, 3, 32

gjamTrimY, 3, 33

par, 18

print.gjam (gjam), 4

summary.gjam (gjam), 4