Package 'powerindexR'

November 6, 2026

Type Package

Title Measuring the Power in Voting Systems

Version 1.7

Date 2026-11-06

Depends R(>= 3.0.0)

Description This R package allows the determination of some distributions of the voters' power when passing laws in weighted voting situations.

License GPL-2

LazyLoad yes

RoxygenNote 7.0.2

NeedsCompilation no

Author Livino M. Armijos-Toro [aut, cre],
Jose M. Alonso-Meijide [aut],
Manuel A. Mosquera [aut],
Alejandro Saavedra-Nieves [aut],
MCIN/AEI/10.13039/501100011033 [fnd] (Projects PID2021-124030NB-C32 and PID2021-124030NB-C33. ERDF A way of making Europe/EU)

Maintainer Livino M. Armijos-Toro <livinoa@gmail.com>

Repository CRAN

Date/Publication 2026-11-06 20:40:02 UTC

Contents

powerindexR-package 2
MWC 3
pi.banzhaf 4
pi.colomermartinez 5
pi.johnston 6
pi.johnstoncolomermartinez 7
pi.shapley 8
powerindex 9
QMWC 10

Index **12**

`powerindexR-package` *Measuring the Power in Voting Systems*

Description

This R package allows the determination of some distributions of the voters' power when passing laws in weighted voting situations.

Details

The DESCRIPTION file:

Package:	powerindexR
Type:	Package
Title:	Measuring the Power in Voting Systems
Version:	1.7
Date:	2026-11-06
Authors@R:	c(person("Livino M.", "Armijos-Toro", role = c("aut", "cre"),email="livinoa@gmail.com"), person("Jose M.'
Depends:	R(>= 3.0.0)
Description:	This R package allows the determination of some distributions of the voters' power when passing laws in we
License:	GPL-2
LazyLoad:	yes
RoxygenNote:	7.0.2
Author:	Livino M. Armijos-Toro [aut, cre], Jose M. Alonso-Meijide [aut], Manuel A. Mosquera [aut], Alejandro Saav
Maintainer:	Livino M. Armijos-Toro <livinoa@gmail.com>

Index of help topics:

```
MWC                     Obtain the minimal winning coalitions
QMWC                    Obtain the quasi-minimal winning coalitions
pi.banzhaf              Power based on the Banzhaf index.
pi.colomermartinez      Power based on the Colomer-Martinez index.
pi.johnston             Power based on the Johnston index.
pi.johnstoncolomermartinez
                        Power based on the Jonhston-Colomer-Martinez
                        index.
pi.shapley              Power based on the Shapley-Shubik index.
powerindex              Obtain several measures of power
powerindexR-package     Measuring the Power in Voting Systems
```

This R package allows the determination of some distributions of the voters' power when passing laws in weighted voting situations.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

This work has been supported under grants PID2021-124030NB-C32 and PID2021-124030NB-C33, funded by MCIN/AEI/10.13039/501100011033 and by "ERDF A way of making Europe".

References

Alonso-Meijide, J. M., & Bowles, C. (2005). Generating functions for coalitional power indices: An application to the IMF. Annals of Operations Research, 137, 21-44. <https://doi.org/10.1007/s10479-005-2242-y>.

Brams, S. J., & Affuso, P. J. (1976). Power and size: A new paradox. Theory and Decision, 7(1-2), 29-56. <https://doi.org/10.1007/BF00141101>.

Colomer, J. M., & Martinez, F. (1995). The paradox of coalition trading. Journal of Theoretical Politics, 7(1), 41-63. <https://doi.org/10.1177/0951692895007001003>.

Johnston, R. J. (1978). On the measurement of power: Some reactions to Laver. Environment and Planning A, 10(8), 907-914. <https://doi.org/10.1068/a100907>.

Lucas, W. F. (1983). Measuring power in weighted voting systems (pp. 183-238). Springer New York. <https://doi.org/10.1007/978-1-4612-5430-0_9>

MWC *Obtain the minimal winning coalitions*

Description

This function determines the minimal winning coalitions in a weighted majority game.

Usage

```
MWC(quota, weights)
```

Arguments

`quota`	Numerical value that represents the majority in a given voting.
`weights`	Numerical vector of dimension n that indicates the weights of n agents in a given voting.

Value

`Number of Minimal Winning Coalitions`
: Total amount of Minimal Winning Coalitions.

`Minimal Winning Coalitions`
: Each row indicates a binary representation of each Minimal Winning Coalition.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

Examples

```
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
MWC(quota,weights)
```

---

pi.banzhaf *Power based on the Banzhaf index.*

Description

This function determines the distribution of the power based on the Banzhaf index and the Banzaf-Owen value.

Usage

```
pi.banzhaf(quota, weights, partition = NULL, normalized = FALSE, swing = FALSE)
```

Arguments

quota	Numerical value that represents the majority in a given voting.
weights	Numerical vector of dimension n that indicates the weights of n agents in a given voting.
partition	Numerical vector that indicates the partition of voters. Each component indicates the element of the partition to which such voter belongs. If it is not NULL, it provides the distribution of the power based on the Banzhaf-Owen value.
normalized	Logical option to obtain the normalized Banzhaf values.
swing	Logical option to obtain the number of swings of each voter.

Value

Banzhaf value	The Banzhaf value, if partition=NULL.
Banzhaf-Owen value	The Banzhaf-Owen value, if partition!=NULL.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

References

Alonso-Meijide, J. M., & Bowles, C. (2005). Generating functions for coalitional power indices: An application to the IMF. Annals of Operations Research, 137, 21-44.

Brams, S. J., & Affuso, P. J. (1976). Power and size: A new paradox. Theory and Decision, 7(1-2), 29-56.

Examples

```
# Example Banzhaf value
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
pi.banzhaf(quota,weights)
pi.banzhaf(quota,weights,normalized=TRUE)

# Example Banzhaf-Owen value
quota<-30
weights<-c(28, 16, 5, 4, 3, 3)
# Partition={{1},{2,4,6},{3,5}}
pi.banzhaf(quota,weights,partition=c(1,2,3,2,3,2))
```

---

pi.colomermartinez *Power based on the Colomer-Martinez index.*

Description

This function determines the distribution of the power based on the Colomer-Martinez index.

Usage

```
pi.colomermartinez(quota, weights, minimal = FALSE)
```

Arguments

quota	Numerical value that represents the majority in a given voting.
weights	Numerical vector of dimension n that indicates the weights of n agents in a given voting.
minimal	Logical option to obtain the Minimal Winning Coalitions.

Value

`Colomer-Martinez`
: The Colomer-Martinez index.

`Number of Minimal Winning Coalitions`
: Total amount of Minimal Winning Coalitions.

`Minimal Winning Coalitions`
: Each row indicates a binary representation of each Minimal Winning Coalition.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

References

Colomer, J. M., & Martinez, F. (1995). The paradox of coalition trading. Journal of Theoretical Politics, 7(1), 41-63.

Examples

```
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
pi.colomermartinez(176,weights,minimal=TRUE)
```

`pi.johnston` *Power based on the Johnston index.*

Description

This function determines the distribution of the power based on the Johnston index.

Usage

```
pi.johnston(quota, weights, quasiminimal = FALSE)
```

Arguments

`quota`	Numerical value that represents the majority in a given voting.
`weights`	Numerical vector of dimension n that indicates the weights of n agents in a given voting.
`quasiminimal`	Logical option to obtain the Quasi-Minimal Winning Coalitions.

Value

`Johnston`	The Jonhston index.
`Number of Quasi-Minimal Winning Coalitions`	Total amount of Quasi-Minimal Winning Coalitions.
`Quasi-Minimal Winning Coalitions`	Each row indicates a binary representation of each Quasi-Minimal Winning Coalition.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

References

Johnston, R. J. (1978). On the measurement of power: Some reactions to Laver. Environment and Planning A, 10(8), 907-914.

Examples

```
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
pi.johnston(176,weights,quasiminimal=TRUE)
```

`pi.johnstoncolomermartinez` *Power based on the Jonhston-Colomer-Martinez index.*

Description

This function determines the distribution of the power based on the Jonhston-Colomer-Martinez index.

Usage

```
pi.johnstoncolomermartinez(quota, weights)
```

Arguments

`quota`	Numerical value that represents the majority in a given voting.
`weights`	Numerical vector of dimension n that indicates the weights of n agents in a given voting.

Value

`Jonhston-Colomer-Martinez`
: The Jonhston-Colomer-Martinez index.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

References

Colomer, J. M., & Martinez, F. (1995). The paradox of coalition trading. Journal of Theoretical Politics, 7(1), 41-63.

Johnston, R. J. (1978). On the measurement of power: Some reactions to Laver. Environment and Planning A, 10(8), 907-914.

Examples

```
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
pi.johnstoncolomermartinez(176,weights)
```

`pi.shapley` *Power based on the Shapley-Shubik index.*

Description

This function determines the distribution of the power based on the Shapley-Shubik index and the Owen value.

Usage

```
pi.shapley(quota, weights, partition = NULL)
```

Arguments

`quota`	Numerical value that represents the majority in a given voting.
`weights`	Numerical vector of dimension n that indicates the weights of n agents in a given voting.
`partition`	Numerical vector that indicates the partition of voters. Each component indicates the element of the partition to which such voter belongs. If it is not `NULL`, it provides the distribution of the power based on the Owen value.

Value

`Shapley value`	The Shapley value, if `partition=NULL`.
`Owen value`	The Owen value, if `partition!=NULL`.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

References

Alonso-Meijide, J. M., & Bowles, C. (2005). Generating functions for coalitional power indices: An application to the IMF. Annals of Operations Research, 137, 21-44.

Lucas, W. F. (1983). Measuring power in weighted voting systems (pp. 183-238). Springer New York.

Examples

```
# Example Shapley value
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
pi.shapley(quota,weights)

# Example Owen value
quota<-30
weights<-c(28, 16, 5, 4, 3, 3)
# Partition={{1},{2,4,6},{3,5}}
pi.shapley(quota,weights,partition=c(1,2,3,2,3,2))
```

`powerindex` *Obtain several measures of power*

Description

This general function allows the determination of several distributions of the power under different approaches in a weighted voting situation.

Usage

```
powerindex(quota, weights, index = c("S", "B", "J", "CM", "JCM"),
partition = NULL, quasiminimal = FALSE, minimal = FALSE, normalized = FALSE,
swing = FALSE)
```

Arguments

`quota`	Numerical value that represents the majority in a given voting.
`weights`	Numerical vector of dimension n that indicates the weights of n agents in a given voting.
`index`	Character that indicates the used approach. `S` and `B` denote the Shapley-Shubik index and the Banzhaf index, and the Owen index and the Banzhaf-Owen index if `partition` exist. `J` is used for obtaining the Jonhston index, `CM` determines the Colomer-Martinez index and `JCM` is used for obtaining the Jonhston-Colomer-Martinez index.
`partition`	Numerical vector that indicates the partition of voters. Each component indicates the element of the partition to which such voter belongs.
`quasiminimal`	Logical option to obtain the Quasi-Minimal Winning Coalitions.
`minimal`	Logical option to obtain the Minimal Winning Coalitions.
`normalized`	Logical option to obtain the normalized Banzhaf values.
`swing`	Logical option to obtain the number of swings of each voter.

Value

See the values of the respective functions.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

References

Alonso-Meijide, J. M., & Bowles, C. (2005). Generating functions for coalitional power indices: An application to the IMF. Annals of Operations Research, 137, 21-44.

Brams, S. J., & Affuso, P. J. (1976). Power and size: A new paradox. Theory and Decision, 7(1-2), 29-56.

Colomer, J. M., & Martinez, F. (1995). The paradox of coalition trading. Journal of Theoretical Politics, 7(1), 41-63.

Johnston, R. J. (1978). On the measurement of power: Some reactions to Laver. Environment and Planning A, 10(8), 907-914.

Lucas, W. F. (1983). Measuring power in weighted voting systems (pp. 183-238). Springer New York.

Examples

```
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
powerindex(quota,weights,index="S")
powerindex(quota,weights,index="B",swing=TRUE)
powerindex(quota,weights,index="B",partition=c(1,1,2,2,3,3,4,4,4),swing=TRUE)
powerindex(quota,weights,index="J",quasiminimal=TRUE)
```

QMWC *Obtain the quasi-minimal winning coalitions*

Description

This function determines the quasi-minimal winning coalitions in a weighted majority game.

Usage

```
QMWC(quota, weights)
```

Arguments

quota	Numerical value that represents the majority in a given voting.
weights	Numerical vector of dimension n that indicates the weights of n agents in a given voting.

Value

`Number of Quasi-Minimal Winning Coalitions`
: Total amount of Quasi-Minimal Winning Coalitions.

`Quasi-Minimal Winning Coalitions`
: Each row indicates a binary representation of each Quasi-Minimal Winning Coalition.

Author(s)

Livino M. Armijos-Toro, Jose M. Alonso-Meijide, Manuel A. Mosquera, Alejandro Saavedra-Nieves.

Examples

```
weights<-c(137,85,71,32,9,8,5,2,1)
quota<-176
QMWC(quota,weights)
```

Index

∗ **powerindex**
powerindexR-package, 2

MWC, 3

pi.banzhaf, 4
pi.colomermartinez, 5
pi.johnston, 6
pi.johnstoncolomermartinez, 7
pi.shapley, 8
powerindex, 9
powerindexR *(*powerindexR-package*)*, 2
powerindexR-package, 2

QMWC, 10