

Package ‘xtrec’

September 30, 2026

Type Package

Title Panel Unit Root Test Based on Recursive Detrending

Version 1.0.1

Description Implements the recursively detrended panel unit root tests proposed by Westerlund (2015) <[doi:10.1016/j.jeconom.2014.06.015](https://doi.org/10.1016/j.jeconom.2014.06.015)>. Two variants are provided: the basic t-REC test assuming iid errors, and the robust t-RREC test that accounts for serial correlation, cross-sectional dependence, and heteroskedasticity via defactoring and BIC-selected lag augmentation. Both tests have a standard normal null distribution requiring no mean or variance correction. The panel must be strongly balanced.

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.2

Depends R (>= 3.5.0)

Imports stats

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

URL <https://github.com/muhammedalkhalaf/xtrec>

BugReports <https://github.com/muhammedalkhalaf/xtrec/issues>

NeedsCompilation no

Author Muhammad Alkhalaf [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0002-2677-9246>>)

Maintainer Muhammad Alkhalaf <muhammedalkhalaf@gmail.com>

Repository CRAN

Date/Publication 2026-09-30 21:30:02 UTC

Contents

grunfeld_data	2
print.xtrec	2
summary.xtrec	3
xtrec	3
Index	5

grunfeld_data	<i>Grunfeld Investment Data</i>
---------------	---------------------------------

Description

A balanced panel dataset for 5 large US corporations over 20 years (1935-1954).

Usage

grunfeld_data()

Value

A data frame with columns: firm, year, invest, mvalue.

References

Grunfeld, Y. (1958). *The Determinants of Corporate Investment*. PhD thesis, University of Chicago.

Examples

```
dat <- grunfeld_data()
head(dat)
```

print.xtrec	<i>Print Method for xtrec Objects</i>
-------------	---------------------------------------

Description

Prints a formatted summary of an "xtrec" test result.

Usage

```
## S3 method for class 'xtrec'
print(x, ...)
```

Arguments

x An object of class "xtrec".
 ... Additional arguments (ignored).

Value

Invisibly returns x.

summary.xtrec	<i>Summary Method for xtrec Objects</i>
---------------	---

Description

Prints a summary of an "xtrec" test result.

Usage

```
## S3 method for class 'xtrec'
summary(object, ...)
```

Arguments

object An object of class "xtrec".
 ... Additional arguments (ignored).

Value

Invisibly returns object.

xtrec	<i>Panel Unit Root Test Based on Recursive Detrending</i>
-------	---

Description

Implements the t-REC and t-RREC panel unit root tests of Westerlund (2015). The t-REC assumes iid errors; the robust t-RREC accounts for serial correlation, cross-sectional dependence, and heteroskedasticity.

Usage

```
xtrec(data, var, panel_id, time_id, trend = 0L,  
      robust = FALSE, maxlag = -1L)
```

Arguments

<code>data</code>	A data frame in long format.
<code>var</code>	Character. Name of the variable to test.
<code>panel_id</code>	Character. Name of the panel identifier variable.
<code>time_id</code>	Character. Name of the time variable.
<code>trend</code>	Integer. Polynomial trend degree: 0 (constant only), 1 (linear trend), or 2 (quadratic trend).
<code>robust</code>	Logical. If TRUE, compute the robust t-RREC test.
<code>maxlag</code>	Integer. Maximum lag for BIC selection (-1 for automatic).

Value

An object of class "xtrec" containing the test statistic, p-value, and panel summary statistics.

References

Westerlund, J. (2015). The effect of recursive detrending on panel unit root tests. *Journal of Econometrics*, 185(2), 453-467. doi:[10.1016/j.jeconom.2014.06.015](https://doi.org/10.1016/j.jeconom.2014.06.015)

Examples

```
dat <- grunfeld_data()
res <- xtrec(dat, var = "invest", panel_id = "firm",
             time_id = "year", trend = 0L, robust = FALSE)
print(res)
```

Index

- * **datasets**
 - grunfeld_data, [2](#)
- * **htest**
 - xtrec, [3](#)
- * **print**
 - print.xtrec, [2](#)
 - summary.xtrec, [3](#)

grunfeld_data, [2](#)

print.xtrec, [2](#)

summary.xtrec, [3](#)

xtrec, [3](#)